


DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 19, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Amerada Petroleum Corporation State D Well No. 5 in the

Company or Operator NE NW 1 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,  
Monument-Paddock Field, Lea County.

The dates of this work were as follows: April 16-19, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 16, 19 48  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5215' Total Depth, Lime. Ran temperature survey and found top of cement at 1508', 111% fill. Nipped up 5 1/2" Casing and drilled out cement with 4-3/4" bit from 5136' to 5212'. Tested 5 1/2" Casing with 1100# for 30 minutes before and after drilling cement and OK. Displaced mud with water and strapped tubing out of hole: 5212' equals 5213' BOD. Perforated with Lane Wells from 5150' to 5160', 40 holes. Ran Guiberson Hookwall Packer and 166 jts. of 2-3/8" OD, 4.7# Tubing with 1-3' perf. sub on bottom bull plugged, 1-4' handling sub and 1-8' sub on top. Displaced water with 106 bbls. oil and set packer at 5104' with bottom of tubing at 5205'.

Witnessed by K. V. StephensonAmerada Petroleum Corporation

Foreman

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

19th. day of April 19 48Name Will Hailer TaylorPosition Asst. Dist. Supt.Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date APR 23 1948

Title

100