DISTRIBUTION		E 0.1-4
		Form C-103
	NEW MEXICO OIL CONSERVATION COMMISSION	Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE		0. 0.
U.S.G.S.	, ro Zii	Je Indicate Type of Lease
LAND OFFICE		State Fee
OPERATOR		5. State Oil & Gas Lease No.
		B-1386
SLIN	DRY NOTICES AND DEPORTS ON WELLS	mannanna da
(DO NOT USE THIS FORM FOR	DRY NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. CATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	
•	(FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL WELL	A=11#5	7. Omr Agreement Nume
. Name of Operator	OTHER-	
·	1 0 AA	8. Farm or Lease Name
. Address of Operator	leum Corporation	State "H"
•	11 1 11 14 4 Admin	9. Well No.
Location of Well	- Hobbs, New Mexico 88240	1
. Location of well	44-	10. Field and Pool, or Wildcat
UNIT LETTER	660 FEET FROM THE South LINE AND 1980 FEET FROM	Monument
THE LINE, SEC	TION 1 TOWNSHIP 208 RANGE 36E	
	TOWNSHIP RANGE NMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3571 ° DF	I.es
6. Ch		
Cnec	k Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
NOTICE OF	INTENTION TO: SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
	OTHER	۲
OTHER		
 Describe Proposed or Completed work) SEE RULE 1103. 	Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
Pulled production of 37851 to 3	stion equipment. Ran cast iron cement retainer se 3795; with 50 sx. Incor cement. Ran string shots pectively ever perforations from 3730; to 3745; 38. 3730; to 3745; with 500 gals. 15% Unisol acid.	t at 37691. Squeezed of 100 and 300 grains Ran tubing and
Pulled production of 3785; to 3 per foot respaction of period per	stion equipment. Ran cast iron cement retainer se 3795; with 50 sx. Incor cement. Ran string shots pectively ever perforations from 3730; to 3745; 38. 3730; to 3745; with 500 gals. 15% Unisol acid.	t at 37691. Squeezed of 100 and 300 grains Ran tubing and

CONDITIONS OF APPROVAL, IF ANY: