

Dually completed as Monument Oil and Eumont Gas as follows:

1. Pulled tubing, rods and pump. Ran Gamma Ray-Neutron.
2. Pumped 45 gallons Calseal and filled up to 3842'. Dumped 12 gallons Hydromits and filled up to 3830'. Ran 123 joints 2-3/8" tubing set at 3817'. Swabbed dry. Ran rods and pump.
3. Pulled tubing, rods and pump. Ran 2-3/8" tubing with 5-1/2" BHEH Sweet Hookwall packer at 3708' and hydraulic holddown at 3706'. Swabbed dry. Treated formation with 1000 gallons 15% NE acid. Injection rate 22 gallons per minute. Swabbed dry. Treated formation with 2000 gallons 15% NE acid. Injection rate 168 gallons per minute. Swabbed dry. Ran rods and pump.
4. Pulled tubing, rods and pump. Ran 5-1/2" Baker Model D production packer set at 3740'. Ran 2-3/8" tubing and GOF circulating valve in closed position at 3774'. Pressured tubing and casing with 300#, no drop in pressure. Pulled tubing.
5. Ran 2-3/8" tubing with 5-1/2" Baker packer and tested casing at various depths. Pulled tubing and packer.
6. Perforated 5-1/2" casing from 3350-3362', 3368-3428', 3462-3478', 3488-3502' and 3506-3516' with 2, 1/2" jet holes per foot. Ran 2-7/8" tubing with retrievable bridge plug at 3531' and parent packer at 3447'. Washed perforations from 3516-3462' with 500 gallons mud acid. Released packer at 3447'. Washed perforations from 3516-3462' with 500 gallons mud acid. Reset packer at 3447'. Swabbed. Treated formation thru perforations in 5-1/2" casing from 3516-3462' with 5000 gallons refined oil with 1# sand per gallon. Injection rate 9.2 bbls per minute.
7. Set bridge plug at 3447' and parent packer at 3322'. Treated formation thru perforations in 5-1/2" casing from 3350-3428' with 500 gallons 15% NE acid. Treated formation thru perforations in 5-1/2" casing from 3350-3428' with 8000 gallons 24 gravity oil with 1# sand per gallon. Injection rate 10.8 bbls per minute. Set bridge plug at 3531' and parent packer at 3322'. Pulled tubing, bridge plug and parent packer.
8. Ran 120 joints 2-3/8" tubing and GOF circulating valve in closed position at 3702'. Tested tubing with 200#, OK.
9. Flowed at a rate of 4564 MOP with 800# back pressure (Eumont Gas).
10. Opened circulating valve at 3774'. Ran rods and pump. Monument Oil pumped thru 2-3/8" tubing and Eumont Gas flowed thru 5-1/2" casing.

