

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fine
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL GAS WELL OTHER
2. Name of Operator: Amoco Production Company
3. Address of Operator: P. O. Box 68, Hobbs, New Mexico 88240
4. Location of Well: SL/BHL UNIT LETTER B/C 710/10 FEET FROM THE North LINE AND 2410/2475 FEET FROM THE East/West LINE, SECTION 10 TOWNSHIP 19-S RANGE 38-E NMPM.
10. Field and Pool, or Wildcat: Hobbs GSA
15. Elevation (Show whether DF, RT, GR, etc.): 3603.1' GL
12. County: Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The subject well was spud 10-13-83 and drilled to a total depth of 40'. Ran 14" conductor pipe and cemented with 4 yards of Redi-Mix. Moved in and rigged up Aztec Rig #184. Began continuous drilling operations 10-15-83 with a 12-1/4" bit. Drilled to a total depth of 1638'. On 10-17-83, ran 8-5/8" 24# K-55 casing and set at 1638'. Cemented with 925 sx class C cement with 1% CaCl. Circulated out 365 sx of cement. WOC 18 hrs. Pressure tested casing with 600 psi for 30 min. Held OK. Reduced bit to 7-7/8" and resumed drilling.

0+4-NMOCD, H 1-HOU, R. E. Ogden, Rm 21.150 1-F. J.Nash, HOU Rm 4.206 1-CMH 1-Texaco 1-Shell 1-Sun 1-Petro Lewis

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herring TITLE Admin. Analyst DATE 10-20-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR TITLE _____ DATE OCT 24 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
OCT 21 1983
O.C.D.
HOBBS OFFICE