

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 87240
 District II
 811 South First, Artesia, NM 87210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised March 25, 1999

OIL CONSERVATION DIVISION
 2040 South Pacheco
 Santa Fe, NM 87505

WELL API NO.
30-025-35177

5. Indicate Type of Lease
 STATE FEE

6. State Oil & Gas Lease No.
 N/A

7. Lease Name or Unit Agreement Name:
 NORTH MONUMENT / GRAYBURG
 SAN ANDRES UNIT

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
 Oil Well Gas Well Other

2. Name of Operator
Amerada Hess Corporation

8. Well No.
297

3. Address of Operator
P.O. Box 2040 Houston, TX 77252-2040

9. Pool name or Wildcat
EUNICE-MONUMENT G/S ANDRES

4. Well Location
 Unit Letter **B** : **1310** feet from the **NORTH** line and **2525** feet from the **EAST** line
 Section **36** Township **19 S** Range **36 E** NMPM County **LEA**

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3599' GR.

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- OTHER:
- PLUG AND ABANDON
- CHANGE PLANS
- MULTIPLE COMPLETION

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING TEST AND CEMENT JOB
- OTHER: **RUNNING PRODUCTION CASING**
- ALTERING CASING
- PLUG AND ABANDONMENT

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

10-26-00
 RU Bull Rogers Csg crew & run 90 Jts of 5-1/2" 15.5# J-55 LT&C csg set @ 3986', shoe @ 3985', FC @ 3895', ran 13 centralizers. Cmt w/ BJ 850 sx 35:65 POZ + 6% Gel + 5#/sx salt + 1/4#/sx CF (12.6#-1.98). Tail w/ 550 sx class "C" + 1/4#/sx CF + 0.2% CD-32 + 0.6% FL-62 (14.8#-1.33). Displace w/ 95 bbls fresh water @ 6 bbl/min. Final circ w/ 1500 psi. Bump plug w/ 1950 psi @ 10:30 AM MST 10-26-00. Floats held ok, good returns. Circ 180 sx to pit. Reciprocate csg. NU Kvaerner Nat 7-1/6" x 11" 3M Tbg. Hd.
 TURNED OVER TO PRODUCTION

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy David TITLE Prof. Drilling Engineer DATE 10/31/00

Type or print name Betsy David Telephone No. (713) 609-4803

APPROVED BY _____ TITLE _____ DATE 10 31 2000

Conditions of approval, if any:

