

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

DEC 4 AM 9:43

Pool Element Formation Green County LosInitial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 9-12-56Company Gulf Oil Corporation Lease Bell-Ramsey "C" Well No. 1Unit J Sec. 34 Twp. 2S Rge. 17E Purchaser Permian Basin Pipeline Co.Casing 7" Wt. 80# I.D. 6.456" Set at 3534' Perf. \_\_\_\_\_ To \_\_\_\_\_Tubing 2.375" Wt. 4.7# I.D. 1.995" Set at 3671' Perf. \_\_\_\_\_ To \_\_\_\_\_Gas Pay: From 3534' To 3690' L 3671 xG .670 -GL 2160 Bar. Press. 13.2Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single

Single-Bradenhead-G. G. or G.O. Dual

Date of Completion: 6-21-54 Packer None Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (XXXXXXXXXX) (Meter) Type Taps Pipe

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						855.2		855.2		72
1.	1	1.75	468.1	7.1	83	764.0		775.5		24
2.	1	1.75	478.4	12.3	66	706.0		706.6		24
3.	1	1.75	478.2	12.3	69	638.5		638.5		24
4.	1	1.75	467.2	24.7	69	549.9		625.4		24
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wp} F}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	21.49	58.46	481.3	.9786	.9463	1.042	1224
2.	21.49	77.76	492.6	.9943	.9463	1.048	1669
3.	21.49	97.39	492.4	.9925	.9463	1.048	2077
4.	21.49	117.4	480.4	.9925	.9463	1.047	2508
5.							

## PRESSURE CALCULATIONS

G<sub>g</sub> = 1.63%W<sub>g</sub> = 1.03%

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.

Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.

F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)

Specific Gravity Separator Gas \_\_\_\_\_

Specific Gravity Flowing Fluid \_\_\_\_\_

P<sub>c</sub> 568.4 P<sub>c</sub> 754.1

No.	P <sub>w</sub> P <sub>w</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> /P <sub>c</sub>
1.	788.7					622.0	132.1		.92
2.	782.8					612.8	129.3		.94
3.	695.7					484.2	211.9		.80
4.	698.6					488.0	216.3		.78
5.									

Absolute Potential: 4330 MCFPD; n .73COMPANY Gulf Oil CorporationADDRESS Box 2167, Dallas, N.M.AGENT and TITLE Ed. J. Gormet

WITNESSED \_\_\_\_\_

COMPANY \_\_\_\_\_

REMARKS

ELVIS A. UTZ  
ENGINEER

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressability factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .