

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 092096 (a)
Unit H.K.F.U.

Oct 20 1950
OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. K. Lockhart and 7 No. 3-B Hobbs, New Mexico October 20, 1950

Well No. 3-B is located 300 ft. from N line and 1650 ft. from W line of sec. 27

27 (4 Sec. and Sec. No.) 21 (Twp.) 17 East (Range) 107N (Meridian)
DeBaca (Field) Las (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3418 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 20 3/4" casing at 220' and cemented with 200 sacks cement. Cement circulated to surface. Total depth of hole 207' in 2nd leg, Plug down 7:35 A.M. 10-20-50.

On 10-19-50, after 24 hours WOC, tested casing with 250' for 30 minutes. Final pressure 250'. Found top of cement plug at 130'. Drilled out cement plug and tested casing with 250' for 30 minutes. Final pressure 250'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 00

Hobbs, New Mexico

By E. L. Shapiro

Title District Superintendent

(a) 00000
M.E.S.B.

I

02	ES	00000	00000	00000	00000	00000	00000
25	27	00000	00000	00000	00000	00000	00000
		00000	00000	00000	00000	00000	00000

00000

00000 00000 00000 00000 00000 00000 00000 00000

00000 00000 00000 00000 00000 00000 00000 00000

00000 00000 00000

00000

00000 00000

00000 00000 00000