

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 25 1 10 PM '66

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. B-1557
7. Unit Agreement Name
8. Farm or Lease Name STATE TRACT 13
9. Well No. 5
10. Field and Pool, or Wildcat WANTZ ABO
12. County LEA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☒ OTHER-
2. Name of Operator Pan American Petroleum Corp.
3. Address of Operator Box 68, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER E 1980 FEET FROM THE NORTH LINE AND 660 FEET FROM THE WEST LINE, SECTION 36 TOWNSHIP 21-S RANGE 37-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3371 D.F.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☒ Deepening & Recompletions

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Prior to deepening, tested 7" casing to 1000 psi for 30 minutes. Test O.K.

Squeezed each zone, Blinney and Drinkard, w/ 250 sq cement, each. Drilled out to a new total depth of 7564'. Ran logs. Set 4 1/2" liner from 6411 - 7564, cemented w/ 250 sq. Drilled out to PBD of 7373'. Perforated 6955-56, 61-64, 65-66, 67-68, 72-74, 7006-08, 46-48, 63-64, 88-86, 93-94, 7105-06, 7249-50, 68-70, 85-86 99-01, 7303-04, 18-19, 22-24, 26-27, 30-32' w/ 2SPF. Acidized perfs 7249-7332 w/ 5000 gal 15%. Acidized 6955-7150 w/ 5000 gal 15%. Frack 6955-7332 w/ 40000 gal gel foam, 34500# sand, 3000# balls. Acidized w/ 5000 gal. Evaluated. Set Baker Model D Packer at 6360'. Perforated Subsbm zone 6014-42, 84-6246 w/ 1JSPF. Acidized w/ 15000 gal. Evaluated. Ran dual completion equipment. Shut-in Subt awaiting dual completion authority. Swabbed in + put Abo on production.

OC-5-23-66

Comp 7-25-66

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Area Supt. DATE 7-27-66

043, NMOCC-N

1-NSW

1-KWB

APPROVED BY 1-RRJ

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE