

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1955 AUG 20 AM 8:05

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

August 17, 1955
(Date)

Jal. New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Westates Petroleum Company
(Company or Operator)

Jones
(Lease)

McVay & Stafford
(Contractor)

Well No. **1** in the **SE** $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **1**

T. **203**, R. **38E**, NMPM., **House** Pool, **Lea** County.

The Dates of this work were as follows: **June 14, 1955 to August 8, 1955**

Notice of intention to do the work (was) ~~RECEIVED~~ submitted on Form C-102 on **June 14**, 19**55**
(Cross out incorrect words)

and approval of the proposed plan (was) ~~RECEIVED~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Heavily mudded hole from bottom to top. Cemented with 25 sacks regular cement from 3070' to 3150'. Cut off 8-5/8" head-pat 4" pipe monument in top with 10 aks cement. Hole was tested with D.S.T. from 7170' to 7059'. Recovered 1160' gas in D.P. - 324' gas cut mud. No gas to surface. Tool open 1 hr. I.F.P - 60 P.S.I. F.F.P. - 100 P.S.I.; C.I.P. - 250 P.S.I. after 20 minutes. 300' of 13-3/8" Csg. cmt. to surface left in hole. 3150' of 8-5/8" Csg. Cmt. to surface left in hole; D.V. Tool at 1656' - Cmt. to surface. Cemented around bottom with 230 sacks cement. The pits were filled and location leveled and cleaned August 8, 1955 following moving of rig by Contractor - McVay & Stafford, J. M. Hale, pusher. Work completed entirely Aug. 8, 1955. T. D. 76 05' - No porosity or showing of oil & gas worthy of testing.

Witnessed by **J. M. Hale**
(Name)

McVay & Stafford
(Company)

Tool Pusher
(Title)

Approved:

OIL CONSERVATION COMMISSION

McArmstrong
(Name)

Oil & Gas Inspector
(Title)

AUG 23 1955
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **J. G. Benton**

Position **Division Superintendent**

Representing **Westates Petroleum Corporation**

Address **P. O. Box 1381 - Jal., New Mexico**