

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Recomplete</b>	X

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

**Hobbs, New Mexico**  
(Place)

**May 21, 1963**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Pan American Petroleum Corporation**

**D. E. Howe B** Well No. **1** in **P**  
(Company or Operator) Lessee (Unit)  
**SE** 1/4 **SE** 1/4 of Sec. **11**, T. **20-S**, R. **38-E**, NMPM, **Howe-San Andres** Pool  
(40-acre Subdivision) **Lee** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to abandon the Drinkard-Tubb-Elmhurst formations, presently producing only 1 BOPD x 68 MCFPD, and recomplete in the San Andres. We propose the following procedure: Spot 25 sz cement plug at 7070' to cover the Drinkard perforations 6990-7060'; 25 sz across Tubb perforations 6975-6970' and the Elmhurst perforations 6010'-6075'. Out and pull 5/8" casing from approximately 5500'. Spot 25 sz plug in and out of 5/8" casing stub. Lead hole with mud. Log. Set OI retainer in 9-5/8" casing at 4500' and spot 100 sz cement below retainer and leave 20' cement on top of retainer. San Andres perforations to be determined after review of logs.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

**Pan American Petroleum Corporation**  
Company or Operator

Original Signed By  
By **V. E. Staley**

Position **Area Superintendent**

Send Communications regarding well to:

Name **V. E. Staley**

Address **Box 68 - Hobbs, New Mexico**

