

My Commission expires 8/23/55

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Man Ishne

-

WELL RECORD

Mail to Oil Conservation Commission. Santa Fe, New Mexico, or proper agent not more than twenty days after completion of well. Follow instructions in the Bules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT 1N TRIPLICATE.

								Fred			
					6 Company				ease	_, _{T.} _20	- S
					···			<u>Le</u>	a		Cour
								the East lin		ection	18
								, Address			
								, Address			
	ssee is commen		2/21	•				_, Address_ npleted		-	
								npieted F _, Address_			
					3556			, Address_	marillo	, Texa	3
							iot Coni	Midential			19
						DS OR ZO					
No. 1, fi	rom	370	3	to 39	15	No. 4, f	rom		to		
No. 2, f1	rom			to		No. 5, f	rom		to		74
No. 3, fi	rom		t	to		No. 6, f	rom	·	to		
				1	IMPORTAN'	r water	SANDS				
Include	data on	rate of	water inf	low and e	levation to	which wate	er rose in	hole.			
	from							reet.			
								feet.			
								feet.			
No. 4, 1	from							feet.			
	1		 		CASIN	G RECOR	υ 				
SIZE	WEIGH PER F		THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE		FILLED FR	PERFOR:	TED TO	PURPOSE
-5/8	24#		8-HT	Smls.	2761	Guide					
-1/2	15.5	f .	8-1.7	Smls.	36671	Float			ione -		
				-		<u> </u>		·····			
		1					1				İ
			 								
	1			МПОЛ	DING AND	CEMENTIN	G RECO	RD			<u> </u>
100	gran -						1				
HOLE	SIZE OF CASING	WHER	E SET	NO. SACE OF CEMEN		OD USED	MUI	D GRAVITY	AMO	OUNT OF I	MUD USED
	8-5/8		291'	210	Hallib						
r-7/8	5-1/2	3'	703	1700	Hallit	urton					
_					PLUGS AS	D ADAPI	ERS			_ 	7
eaving	plugM	aterial_			Length			Dept	th Set		
.dapters	—-Materia	ul			Size				- · · · · · · · · · · · · · · · · · · ·		
			RECO	ORD OF	SHOOTING	OR CHEM	HCAL T	REATMENT			
SIZE	SHET	L USED	CHEMI	OSIVE OR	QUANTI	тү	ATE	DEPTH SH		ртн огр	ANED OUT
~:###			 					VICTREAT.	Di		ANED OUT
			PALOUE	S.O. N.		ta 3/2	28/52	37/3' to	39151		
								·			
								LB.S. & 0			
m 10/	64" Ch	oke,	TP 300	· · · · · · ·	Vol. 48,	010 ca 1	t p/d	GO. 488	Gty I	4.3 Co	rrected
							·	·			
					F DRILL-S						
' dr ill-st	tem or ot	he r spe	cial tests	or deviatio			submit r	eport en sep	arate shee	et and att	ach hereto
						LS USED					
								from			
abie too	us wer e t	ised fro	om	f			reet, and	from	feet	to	fee t
11	rodusin =	Ma-	reh 30	1950	PROI	DUCTION					
			•				e eliza -	which. 100	۰		_
					% sedi						%
								er 1,000 cu.			
							_{висоние} р	AL A,CUU CU.	ii. oi gas	·	
OCE IN P.	, 103	E 194		. ————		LOYEES					
ock pre			Stewar	t			. W. N	BY9			Drillow
		C. F.									
					, Drille	r					_ Driller
					, Drille						Driller
	swear or	E. J.	Locke	FORMAT	TION RECO	RD ON C	THER S	SIDE			
hereby		E. J.	Locke that the	FORMAT	TION RECO	ORD ON C	OTHER S				
hereby ork don	e on it so	affirm	that the	FORMATinformatio	rion RECC	ORD ON Crewith is a	OTHER S	SIDE e and correc	et record	of the w	ell and al
hereby ork don abscribe	e on it so	affirm	that the can be de	FORMAT information termined for this	FION RECO	PRD ON Corewith is a cole records.	OTHER S a complet	SIDE e and correc	et record	of the w	ell and al
hereby ork don abscribe	e on it so	affirm	that the can be de	FORMAT information termined for this	FION RECO	PRD ON Corewith is a lie records.	OTHER S	SIDE e and correc	Ap	of the w	ell and al

Representing America Fetroleum Corporation Company or Operator.

Address Drawer , Monument, New Mexico

FROM	то	THICKNESS IN FEET	DRMATION RECORD	ON			
0 6 1404 1510 2525 2650 2790 3480	6 1404 1510 2525 2650 2790 3480 3915 3915	6 1398 106 1015 215 140 690 435	Anhydrite, Red Sano and Shale Salt, Polyhalite and Anhydrite Anhydrite Hed Sand and Anhydrite Dolomite and Anhydrite Dolomite, Anhydrite and Sand Total Depth				
			GEOLOGICAL Top Anhydrite	DA TA 1417°			
			Top Salt Base Salt Top Yates Top Zone #1 Top Monument Lime Top Grayburg	1528 2538 2674 2695 2822 3676			
	SLOPE TEXT	īs.					
800 1 1800 2150 2550	:	-3/4 deg. 1-3/4 1-1/4 2-1/4 -3/4					
30 6 9 3587	:	-3/4					
		<u>N.) E</u>	RILL STEM TASTS				
				•			
	·						