

COPY TO G. C. C.

Form 1-351
1-7-79

Form Approved
Budget Bureau No. 10-61404

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NOTICE, NOTICES AND REPORTS ON WELLS

1. NAME OF OPERATOR

2. ADDRESS OF OPERATOR

3. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)

AT SURFACE: 64-150-1-100-10

AT TOP PROD. INTERVAL: 64-150-1-100-10

AT TOTAL DEPTH: 64-150-1-100-10

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT ON:

TEST WATER SHUT-OFF
FRACTURE TREAT
CROST OR ADDIZL
REPAIR WELL
CUT OR ALTER CASING
MISPLUG COMPLETE
CHANGE LOGS
NEW BOH
OTHER

TEST WATER SHUT-OFF
FRACTURE TREAT
CROST OR ADDIZL
REPAIR WELL
CUT OR ALTER CASING
MISPLUG COMPLETE
CHANGE LOGS
NEW BOH
OTHER

4. LEASE

5. IF INDIAN ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD OR W LOCAT NAME

11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3554' DF

NOTE: Report results of multiple completion or zone
shutoff on Form 9-2301

GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

17. Describe in brief the work done on the well, including the nature of the work, the results of the work, and the date of the work.

The well was drilled to a depth of 6478'-6" and was completed with a 4 1/2" casing. The well was tested at a pressure of 6478'-6" and produced 100 bbls of oil per day. The well was then shut in for 30 days and then tested again at a pressure of 6478'-6" and produced 100 bbls of oil per day. The well was then shut in for 30 days and then tested again at a pressure of 6478'-6" and produced 100 bbls of oil per day.

Subsurface Safety Valve: Manual and Type: Set @ 6478'-6" Ft.

18. I hereby certify that the foregoing is true and correct.

W. B. Hall, District Engineer

APPROVED BY
DATE OF APPROVAL: 10/25/79
W. B. Hall
District Engineer

APPROVED
OCT 25 1979
W. B. Hall
ACTING DISTRICT ENGINEER