

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
PO. Box 460 Hobbs N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL, 990' FWL.
AT TOP PROD. INTERVAL: SAME
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>CONV. TO INJ</u> <input checked="" type="checkbox"/>	

5. LEASE
LC-031695 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
SEMU

8. FARM OR LEASE NAME
SEMU McKEE

9. WELL NO.
60

10. FIELD OR WILDCAT NAME
WARREN McKEE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC 29 T. 20S, R-38E

12. COUNTY OR PARISH LEA. 13. STATE N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3528' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO CONVERT SUBJECT WELL TO INJECTION AS FOLLOWS.

- LOAD WELL W/ TFW.
 - PULL TBG, PKR, VALVES.
 - CLEAN OUT TO T.D IF NECESS.
 - RUN 2 3/8" P.L TBG., W/ PKR SET AT ± 8765'
 - CIRCULATE wellbore w/ 175 BBLs PKR FLUID.
 - FLANGE UP WELL HEAD, PLACE well ON INJECTION.
- NMOCC R-5631 dated 1-24-78

RECEIVED
AUG 15 1978
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ben R. [Signature] TITLE Admin. Supr. DATE 8-17-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

1366 [5] NMAU [4] FILE

*See Instructions on Reverse Side

APPROVED
SEP 8 1978
PAZ
ACTING DISTRICT ENGINEER