

COPIES RECEIVED		
TRIBUTION		
FE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-2663

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Water Injection Well</u> <u>Jalmat</u>	7. Unit Agreement Name <u>Field Yates Sand Unit</u>
2. Name of Operator <u>Gulf Oil Corporation</u>	8. Farm or Lease Name
3. Address of Operator <u>Box 670, Hobbs, New Mexico 88240</u>	9. Well No. <u>100</u>
4. Location of Well UNIT LETTER <u>N</u> , <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>22-S</u> RANGE <u>35-E</u> NMPM.	10. Field and Pool, or Wildcat <u>Jalmat</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3602' GL</u>	12. County <u>Lea</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <u>Plug and Abandon</u> <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4011' TD, 4005' PB.

Pull injection equipment. Set CI BP at 3800' and cap with 5 sacks Class C cement. Displace hole with produced water containing 25 sacks of gel per 100 barrels of water. Spot 15 sack Class C cement plug from 2000' to 1850', across top of salt. Load hole with mud. Spot 50' cement plug from 50' to surface. Install dry hole marker and clean location.

THE OPERATOR MUST BE ADVISED 24 HOURS PRIOR TO THE RESUMPTION OF PLUGGING OPERATIONS FOR THE G-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bryn Stone TITLE Senior Project Engineer DATE May 3, 1974

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: