

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	Drill out Float Collar NOTICE OF INTENTION (OTHER) & Cement to 3940'		NOTICE OF INTENTION (OTHER) Sand-Oil Frac.	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Midland, Texas
(Place)

1 September, 1958
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the The British-American Oil

Producing Company New Mexico "B"
(Company or Operator)

Well No. 1 in P
(Unit)

SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 14, T. 22-S, R. , NMPM, Jalnet
(40-acre Subdivision)

Pool

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Move and rig up double drum unit. Pull Rods and Tubing.
2. Drill out float collar and cement from 3915'-to 3940'.
3. Perforate additional Yates Sand from 3815'-3823' and 3831'-3838'.
4. Run 2" tubing with packer, set packer at 3900' and attempt to establish circulation between 2nd and 3rd bench. Reset packer at 3850' and attempt to establish circulation between 1st and 2nd bench.
5. Reset packer 3900' and sand-oil fracture lower zone 3910'-3932' with 15,000 gallons oil and 15,000 lbs. sand, 200 lbs. "GYPRAN".
6. Set Baker Model K Cast Iron Bridge Plug at 3850'.
7. Fracture upper perforations 3815-3823 and 3831-3838 with 15,000 gallons oil and 15,000 lbs. sand mixed with 200 lbs. "GYPRAN."
8. Drill out bridge plug to PHD.
9. Run tubing and rods and hang well on beam.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

The British-American Oil Producing Co.
Company or Operator

By German B. French
German B. French, District Clerk

Position.....
Send Communications regarding well to:

Name Cecil E. Brandon, District Supt.

Address P. O. Box 474, Midland, Texas

