DISTRIBUTION SANTA FE			Supersedes Old
3ANIA FE	NEW MEXICO OIL CONSE	RVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE			
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State Fee
OPERATOR	. ·		5, State Oil & Gas Lease No.
SUNDR	RY NOTICES AND REPORTS ON W	'ELLS	
(DO NOT USE THIS FORM FOR PRO USE "APPLICAT	POSALS TO DRILL OR TO DEEPEN ON PLUG BAC TON FOR PERMIT - (FORM C-101) FOR SUCH	K TO A DIFFERENT RESERVOIR, Proposals.)	
1. OIL GAS WELL WELL	OTHER. Water Indeets		7. Unit Agreement Name
2. Name of Operator	OTHER- Water Injection	n Well Jalma	Field Yates Sand U-it 8. Form or Lease Name
Gulf Oil Corporation 3. Address of Operator			
			9. Well No.
Box 670, Hobbs, New Med. Location of Well	exico 88240		135
	1980 FEET FROM THE North	330	1
UNIT ELITER	TOM PELT PROM THE	LINE AND PERT PR	
THE East LINE, SECTI	on 14 township 22-S	RANGE HMP	
mmmm	15. Elevation (Show whether D.	E PT CP	
		• •	12. County
18. Chack	Appropriate Box To Indicate Na	' GL.	Lea Allilli
	Appropriate Box To Indicate Na	~	NT REPORT OF:
		· —	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	i	COMMENCE DRILLING OPNS.	PLUS AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	۲
OTHER		V nen	
4111-11			
		Plugged and abandoned	
	perations (Clearly state all pertinent detail		
17. Describe Proposed or Completed Opwork) SEE RULE 1 103.			
17. Describe Proposed or Completed On work) SEE RULE 103.  4000 TD, 3975 PB.  Pulled injection	perations (Clearly state all pertinent details on equipment. Set cement	s, and give pertinent dates, includi	ng estimated date of starting any proposed on a casing with water.
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000 TD, 3975 PB.  Pulled injection Squeezed below retained	oerations (Clearly state all pertinent details on equipment. Set cement er with 45 sacks of cement	s, and give pertinent dates, including retainer at 3590°. I Spotted 5 sack centers.	oaded casing with water.
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole were	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1	retainer at 3590°. I Spotted 5 sack cem O sack cement plug fr	ng estimated date of starting any proposed coaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000 TD, 3975 PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590'. I Spotted 5 sack cem 0 sack cement plug fr surface. Installed	oaded casing with water. ent plug on top of re- com 2000' to 1850', acros
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB. Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus	on equipment. Set cement er with 45 sacks of cement with gel water. Spotted 1 cement plug from 100° to	retainer at 3590°. I Spotted 5 sack cem sack cement plug fr surface. Installed 8, 1974.	oaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB. Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus	on equipment. Set cement or with 45 sacks of cement with gel water. Spotted la cement plug from 100' to agged and abandoned June 1	retainer at 3590°. I Spotted 5 sack cem sack cement plug fr surface. Installed 8, 1974.	oaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000 TD, 3975 PB. Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus	on equipment. Set cement or with 45 sacks of cement with gel water. Spotted 1 cement plug from 100' to agged and abandoned June 1 shows is true and complete to the best of	retainer at 3590°. I Spotted 5 sack cem sack cement plug fr surface. Installed 8, 1974.	oaded casing with water. ent plug on top of re-
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus 18. I hereby certify that the information is a second control of the second	on equipment. Set cement or with 45 sacks of cement with gel water. Spotted la cement plug from 100' to agged and abandoned June 1	retainer at 3590'. I . Spotted 5 sack cem 0 sack cement plug fr surface. Installed 8, 1974.	no estimated date of starting any proposed coaded casing with water. Sent plug on top of remove 2000' to 1850', across dry hole marker and
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB. Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus 18. Thereby certify that the information is a second control of the second c	on equipment. Set cement or with 45 sacks of cement with gel water. Spotted la cement plug from 100' to agged and abandoned June 1	retainer at 3590°. I Spotted 5 sack cem sack cement plug fr surface. Installed 8, 1974.	no estimated date of starting any proposed coaded casing with water. Sent plug on top of remove 2000' to 1850', across dry hole marker and
17. Describe Proposed or Completed On work) SEE RULE 1703.  4000' TD, 3975'PB.  Pulled injection Squeezed below retained tainer. Loaded hole was alt. Spotted 10 sack cleaned location. Plus 18. I hereby certify that the information is a second control of the second	on equipment. Set cement or with 45 sacks of cement with gel water. Spotted la cement plug from 100' to agged and abandoned June 1	retainer at 3590'. I . Spotted 5 sack cem 0 sack cement plug fr surface. Installed 8, 1974.	no estimated date of starting any proposed coaded casing with water. Sent plug on top of remove 2000' to 1850', acrost dry hole marker and