

COPIES RECEIVED		
TRIBUTION		
FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-8173	

## SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Water injection Well</b>		7. Unit Agreement Name
2. Name of Operator <b>Gulf Oil Corporation</b>		8. Farm or Lease Name <b>Field Yates Sand Unit</b>
3. Address of Operator <b>Box 670, Hobbs, New Mexico 88240</b>		9. Well No. <b>135</b>
4. Location of Well UNIT LETTER <b>H</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>330</b> FEET FROM THE <b>East</b> LINE, SECTION <b>14</b> TOWNSHIP <b>22-S</b> RANGE <b>35-E</b> NMPM.		10. Field and Pool, or Wildcat <b>Jalmat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3589' GL</b>		12. County <b>Lea</b>

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER **Plug and abandon** ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4000' TD, 3975' PB.

Pull injection equipment. Set CI cement retainer at 3590' and squeeze 45 sacks of Class C cement below retainer. Spot 5 sack Class C cement plug from retainer to 3515'. Displace hole with water containing 25 sacks of gel per 100 barrels of water. Spot 10 sack Class C cement plug from 2000' to 1850', across top of salt. Load hole with mud. Spot cement plug from 50' to surface. Install dry hole marker and clean location.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Glyn Stone*

TITLE Senior Project Engineer

DATE May 3, 1974

APPROVED BY Orig. Signed By Joe D. Perry Dist. L. Supv.

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: