NO. OF COPIES RECEIVED		Form C	-103	
DISTRIBUTION		11088S OF F30 Frag	de Cd	
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective	nd C-103 re 1-1-65	
FILE		JUN 30 3 10 P	M '67	
U.S.G.S.			Type of Lease	
LAND OFFICE		State		
OPERATOR		l l	& Gas Lease No.	
CUNDO	VALOTIOES AND DEPONDED ON WITH	11111	- 396	
USE "APPLICAT	Y NOTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERV ON FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)			
I. OIL X GAS WELL X	OTHER-	Jalmat.	eement Name Cone Yates Pool Unit	
2. Name of Operator J. R.	CONE	8. Farm or	Lease Name Tract 6	
3. Address of Operator	74 Tubback Paras Police	9. Well Nc.	F '	
4. Location of Well	71, Lubbock, Texas 79408	10 71 1	5	
	980 FEET FROM THE South LINE AND 990		nat (Oil)	
THE Bast LINE SECTION	N 24 TOWNSHIP 22-South RANGE 35-East			
THE LINE, SECTION	N TOWNSHIP RANGE	MPM.		
	15. Elevation (Show whether DF, RT, GR, etc.) 3579 Gr; 3590 KB (datum)	12. County Lea		
16. Check	appropriate Box To Indicate Nature of Notice, Rep	 _		
NOTICE OF IN		SEQUENT REPORT	OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK		ALTERING CASING	
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	<u> </u>	PLUG AND ABANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT .	_		
	OTHER			
OTHER				
WORK) SEE ROLE 1103.	erations (Clearly state all pertinent details, and give pertinent date TD 3850; 5½" casing cemented 3844 (2-s			
150 sx thm DV too	1. $9 \cdot 1640^{\circ}$); PBTD 3842°. Initial complet	on as oil well	March 1 1957.	
Casing perforated:	3614-3644 (Yates Zone I) 4 SPF; 3660-3	666 (Yates Zone	TT) 4 snf:	
3768 and 3774 (Yat	es Zone IV) 3 FI holes at each spot; and	3800 (Yates Zo	one V) 3 FI holes	
State and State and and an area are area from State and and are area.				
Work-over to open Yates Zone III and selectively frac same. WO dates 5/30-6/22/67.				
Pulled rods, pump and tubing. Schlumberger jet perforated with one 3/8" hole each at				
	opposite Yates Zone III. Ran Baker r			
36831. Frac'd new	Zone III perfs via 2-7/8" tubing with 3	000 gal. gelled	d, treated	
brine plus 2000 lb	20/40 sd and 2000 lb 10/20 sd. AIR 7 B	M at 2200 psig.	ISDP 1000	
	um in 20 minutes. Pulled packers. Ran			
	tension anchor and bottom seating nippl 11 3/4" rod string. Recovered all load.			
	bumped 51 BO + 67 BW.	men on 19-not	ir cest	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	- In the second			
18. I hereby certify that the information	above is true and complete to the best of my knowledge and belief.			
To Store	0 31-2		June 20 40/2	
SIGNED I'V VICENTY	L. O. Storm HITLE Engineer	DATE_	June 30, 1967	

CONDITIONS OF APPROVAL, IF ANTI-

NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION		Supersedes Old C-102 and C-103
ANTAFE	NEW MEXICO OIL CONSERVATION COMMISS	
TILE		
J.S.G.S.		Sa. Indicate Type of Lease
AND OFFICE		State K
PERATOR		5. State Oil & Gas Lease No.
		E-396-2
SUI	NDRY NOTICES AND REPORTS ON WELLS REPORTS ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESILICATION FOR PURPLY AND POPOSALS.)	
USE **APPL	ICATION FOR PERMIT -** (FORM C-101) FOR SUCH PROPOSALS.)	SERVOIR.
OIL GAS WELL WELL		7. Unit Agreement Name Cone
Name of Operator	OTHER-	Jalmat Yates Pool Unit
•	COME	
. Address of Operator	CONE	Tract 6
	Box 871, Lubbock, Texas 79408	5, 11011 1101
Location of Well	DOX Off, DUDDOCK, 18X25 /9400	10. Field and Pool, or Wildcat
 T	1980 FEET FROM THE South LINE AND 990	·
UNIT LETTER	1980 FEET FROM THE South LINE AND 990	FEET FROM
East Inc.	ECTION 24 TOWNSHIP 22-S BANGE 35-1	
THELINE, S	ection 24 township 22-S RANGE 35-1	NM 2M.
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3579 Est Or: 3590 DF	Lea
Che		
	ck Appropriate Box To Indicate Nature of Notice, I	-
NOTICE O	FINTENTION TO.	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	
TEMPORARILY ABANDON	COMMENCE DRILLING O	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEM	
SEE SH HELEN SHISHES	——————————————————————————————————————	out and install beam pump
OTHER		
	ed Operations (Clearly state all pertinent details, and give pertinent	
bottom and 150 sad 3660-3666 with 4 S Set Bethleham 57 I Tagged bottom with 3755 Cleaned eut Seating nipple at reds. Kicked off	TD 3850; 5-1/2" 14 lb casing comented as the start of the	casing perforated 3614-3644, es 3608. motor on percast concrete base. 1755. Drilled bridge plug at 17. Notched collar on bottom. in 94-5/8" rods and 48-3/4"
8. I hereby certify that the information of the last o	ation above is true and complete to the best of my knowledge and be - L. O. Storm TITLE Engineer	DATE June 9, 1965
, ,		

DATE_