

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030132 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Closson

9. WELL NO.

#5

10. FIELD AND POOL, OR WILDCAT

South Eunice

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18-22S-36E

12. COUNTY OR PARISH 13. STATE

Lea N Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Cities Service Oil Company

3. ADDRESS OF OPERATOR
Hobbs Pipe & Supply P O Box 2010 Hobbs, N M

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

G-1980' FNL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3597'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spotted a 25 sx. cement plug at 3660'-3780'.
2. Spotted a 25 sx. cement plug at 2805'-stub of 5 1/2" casing.
3. Spotted a 25 sx. cement plug at 805'-stub of 8 5/8" casing.
4. Spotted a 25 sx. cement plug at 186'-shoe of 13" casing.
5. Spotted a 10 sx. cement plug at surface with marker.
6. Hole was loaded with mud laden fluids.

Handwritten: P & A 8-21-70

18. I hereby certify that the foregoing is true and correct

SIGNER

Handwritten signature: H. Schneider

TITLE

Agent

DATE

8-21-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Stamp: FEB 4 1975

*See Instructions on Reverse Side