

COPY TO O. C. G.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
CONTINENTAL OIL CO.
3. ADDRESS OF OPERATOR  
P.O. Box 460 Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL + 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- |                                     |                          |                          |
|-------------------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF                 | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT                      | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE                    | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL                         | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING                | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE                   | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES                        | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON*                            | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) spud well, set surf. csq. X |                          |                          |

RECEIVED

MAR 30 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-25-79 spud well  
3-26 dld to 1510' surf csq TD.  
ran csq as follows:  
GS, FC, 35jts 9 5/8", 36", K-55 csq  
set @ 1510' KB. (1499' GL).  
3-27 cmt @ follows:  
pmp. 100 bbl fresh water  
400sx class C" cmt + addit.  
tail in w/ 200sx class C" cmt.  
CIVE 50sx to surf.  
WOC 18 hrs. test to 1000psi: holdok.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Admin. Supv. DATE 3-29-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

USGS -5  
NMFU 4

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD  
MAR 30 1979  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO