

CASING, CENTRALIZERS & SCRATCHERS

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)

FROM-TO	OD	DRIFT ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
							1000 LBS	1000 LBS	
(S) 0-1450'	9 5/8"	8.765	36#	K-55	ST & C	1450'	52.2		
(P) 0-6760'	7"	6.151	26#	K-55	LT & C	6760'	175.76		Sand Blast 800' of casing across Blinebr & Tubb zones.

DV Tool @ +4000'

CENTRALIZERS
INTERVAL
NO. FROM-TO

OTHER ACCESSORY EQUIPMENT
(SUCH AS DEGRASSERS, MUD, CENTRIFUGE
FLOAT COLLARS, ETC. - SPECIFY)

REMARKS

(S) Surface	(4) 2 ea. on bottom two joints (9) 1 every 4 jts. to surface	Guide shoe and float collar
(P) Production	(4) 2 ea. on bottom two joints (8) 1 every 3 joints to 5700'	Float shoe, float collar DV Tool @+4000'