

CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
 State  Fee   
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

WELL  GAS WELL  OTHER

Name of Operator  
Chevron U.S.A. Inc.

Address of Operator  
P.O. Box 670 Hobbs, NM 88240

WELL LETTER B 865 FEET FROM THE North LINE AND 1980 FEET FROM  
East LINE, SECTION 31 TOWNSHIP 21S RANGE 37E N.M.P.M.

7. Unit Agreement Name  
Eunice Monument  
South Unit

8. Farm or Lease Name

9. Well No.  
135

10. Field and Pool, or Wildcat  
Eunice Monument G/SA

15. Elevation (Show whether DF, RT, GR, etc.)  
3529.8'

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

WELL REMEDIAL WORK   
 PARTIALLY ABANDON   
 OR ALTER CASING

PLUG AND ABANDON   
 CHANGE PLANS   
 OTHER

SUBSEQUENT REPORT OF:

REMEDIAL WORK   
 COMMENCE DRILLING OPNS.   
 CASING TEST AND CEMENT JOBS   
 OTHER Completion   
 ALTERING CASING   
 PLUG AND ABANDONMENT

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed operations) SEE RULE 1103.

7-17-87 Log w/ GR/CCL/CBL/CET from PBTD 3909 to 3000, Perf w/1JHPF 0° phased, 3876-56 (20 shots). 3846-3828-18, 3818-3790 (29 shots) total 66 shots, acidize w/100 gallons 15% NEFE HCL across perfs 3876-3790. Acidize w/5000 gallons 15% NEFE. Swab. Sqz perfs 3790-3876 w/300sx Class C. WOC 24 hrs. Tag cmt at 3677, est. circ, w/ CBW. Drill out cmt from 3677 to 3850, circ hole. Perf w/4" guns 1 JHPF, 46 holes, f/3790' to 3818, 3828-3846, spot 100 gallons 20% HCL f/3841-3741. Acidz perfs f/3790-3846 w/1900 gallons 20% HCL. Displace w/CKF to bottom perf, swab. Sqz perf f/3790. - 3846, 46 holes, w/200sx Class C Displace w/ FW. Left 194 sx in formation, 4 sx below retainer, 2 sx above retainer, WOC 24 hours. GIH, tag cmt at 3737', drld cmt to 3817. Circ clean, tst casing 1000psi, ok. Disp hole w/ CKF. Perf w/4" guns 1 JHPF, 180 deg phased, 20 shots f/3780 - 3809. Spot 100 gallons 20% HCL f/3810-3710. Acidz perf f/3790-3809 20 holes w/ 900 gal 20% HCL; Swab, Ran prod. equip, clean location, turn over to production 7-27-87 8-9-87 MIRU, poh prod. equipment, perf w/4" guns 1 JHPF 180 deg phased 26 holes at 3653-68', 3686-91, 3716-20, 3752-54, spot 100 gallons 15% HCL across perfs, f/3754-3653, acidz perfs f/ 3653-to 3754 w/2000 gal 15% NEFE HCL. Swab, Run prod tbq. NDBOP, NUWH, Run prod equip, turn over to production. Work performed 7-17-87 through 8-10-87

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
*Jerry Sexton* TITLE Staff Drilling Engineer DATE August 19, 1987

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT SUPERVISOR

COPIES OF APPROVAL, IF ANY: TITLE DATE