

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-025-34061
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Sharps
8. Well No.	2
9. Pool name or Wildcat	Blinebry Oil & Gas (06660)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Collins & Ware, Inc.

3. Address of Operator
508 West Wall, Suite 1200, Midland, Texas 79701

4. Well Location
Unit Letter N : 660 Feet From The South Line and 1980 Feet From The West Line

Section 13 Township 20S Range 38E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3568' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Perforate and stimulate ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/01/97 Tag PBDT at 7070'. Run CET from 7070' - 3500'. Cement bond looked good all the way.
9/03/97 Perf Tubb interval from 6529' - 6799' with 4" select fire guns.
9/04/97 Acidized perfs 6529' - 6799' with 2500 gals 15% Ferchek SC acid. RU swab and swab dry in 5 runs. Set CIBP at 6480' and dumped 4 sx cement on top of plug.
9/0 /97 Tag PBDT at 6451'. Conventionally perf Blinebry intervals 5977' - 80', 5987' - 97', 6029' - 49', 6090' - 6110', 6190' - 98' with 1 SPF (total 61 perfs). Set packer at 5890'. Acidize perfs with 3000 gals 15% Ferchek SC with ball sealers. Had fair ball action.
9/06/97 Fracture well down casing with a total of 49,500 gals Delta Frac 25 and 139,000# 20/40 Ottawa sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dianne Sumrall TITLE Production Supervisor DATE 9/15/97

TYPE OR PRINT NAME Dianne Sumrall

TELEPHONE NO. (915) 687-3435

(This space for State Use)

ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE 107 - 2 1997

CONDITIONS OF APPROVAL, IF ANY: