

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

February 15, 1949  
DateHobbs, New Mexico  
Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Cities Service Oil Company State NM Well No. 1 in the  
Company or Operator Lease  
Northeast Quarter of Sec. 16, T. 21-S, R. 34-E, N. M. P. M.,  
West Wilson Field, Lea County.

The dates of this work were as follows: February 7, 1949 to February 10, 1949, inclusive

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on February 8 1949  
and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was drilled to a total depth of 3991' in lime. 9-5/8" casing was set at 245.26 and cemented with 200 sacks. 7" casing was set at 3732' and cemented with 400 sacks. Well was swabbed 12 hours and recovered 142 bbls. of water and approximately 2 bbls. of oil. Unable to lower fluid below 1100' from bottom. Well was making 100% black sulphur water. The hole was loaded with heavy mud; 50 sacks cement was run at bottom of hole; 25 sacks at 1081' where 7" casing was shot off and then plugged surface pipe with 50 sacks of cement. A 4'-4" marker was left at location, capped with a 4" bull plug.

Witnessed by R. W. Ely Name Cities Service Oil Company District Superintendent Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

15th day of February 1949

Name \_\_\_\_\_

Position District SuperintendentRepresenting Cities Service Oil Company  
Company or Operator

Drawer "G"

My commission expires March 12, 1951Address Hobbs, New Mexico

Remarks:

Roy Yarbrough  
Name  
Title