

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

SEP 4 - 1945

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Roswell, New Mexico

Place

Aug. 31, 1945

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

The Vickers Petro. Co. Inc. Shell-State Well No. 1 in CNW NE 4
Company or Operator Lease
of Sec. 17 T. 21S. R. 34E N. M. P. M., Dilcat Field,
County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

We propose to plug the above well in the following manner:

We will set a cement plug, consisting of five sacks of cement, at the bottom of the hole (total depth 4116') and then fill the hole with mud to a depth of about 3750' and there set another cement plug at the base of the salt. The hole will then be filled with mud to a depth of about 1950' where another cement plug will be set in the anhydrite above the salt. We will then attempt to pull the 7" casing after it has been broken off above the cemented portion. The hole will then be filled with mud to a depth of about 200' where another cement plug will be set. The 10" casing is cemented to the surface and will be left in the hole. The hole will then be filled with mud to the surface. The top of the hole will be cemented and a regulation marker will be set in cement. The collar and pits will be filled and the surface cleaned up.

Approved

SEP 4 1945

, 19

except as follows:

The Vickers Petro. Co. Inc.

Company or Operator

By

Amos L. Bunte

Position

Geological Engineer

Send communications regarding well to

Name

The Vickers Petro. Co. Inc.

Address

Box 6713

Roswell, New Mexico.

OIL CONSERVATION COMMISSION,

By

Roy Yarbrough

Title