

NEW MEXICO STATE LAND OFFICE
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Hobbs

N. Mex., 6-50-34, 19

Mr. E.H. Wells.

State Geologist,
Santa Fe, New Mexico.

Dear Sir:

State C-20

You are hereby notified that we intend to test the shut-off of water in
Well No. 1 in NW 1/4 of Sec. 20, T. 21S, R. 36E,
N. M. P. M., Banice Oil Field, Lea County,
on 7-3-34 19 9-5/8" 30# lb. casing was cemented in Anhydrite
formation at a depth of 1435 feet on Sam June 30th 19 34
300 sacks of Eltore cement were used.

The method used in placing the cement was as follows:
Pumped in by Halliburton Method.

Fluid level will be bailed to a depth of 1435 feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows: Getty Oil Co.

Additional information: Hole Drilled to 1445' in Anhydritic and 9-5/8"
Casing swung at 1435' and cemented with 300 sacks of cement.
Top of Salt 1390 to 1435'. For water shut off test, 600# Pressure
will be put on casing before drilling plug and left 30 Mins. After
drilling Plug 600# Pressure will be put on casing and left 30 mins.

DUPLICATE

Approved JUL 6 - 1934 19 Sincerely yours,

Continental Oil Co.

Except as follows:

Company or Operator.

By J.E. Warren

Position District Supt.

Send communication regarding well to

Name Contl Oil Co. Dist. Supt.

Address P.O. Box 60 Hobbs N. Mexico.

State Geologist or Oil and Gas Inspector.

3 Copies Returned 7-6-34