

**TRIPPLICATE**

# **OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

## **MISCELLANEOUS REPORTS ON WELLS**

**RECEIVED**

OCT 26 1951

OIL CONSERVATION COMMISSION  
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |          |  |  |
|--|----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |          | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |          | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | <b>X</b> | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |          |  |  |

October 23, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Stanolind Oil and Gas Company Southland Royalty Co. "A" Well No. 4 in the

SE/4 Company or Operator of Sec. 4, T. 21<sup>3</sup>, R. 37-E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: October 19-20-21, 1951

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on October 19 1951  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### **DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

On October 21, 1951 at 11:15 P.M. 43 hours had elapsed after cementing new 8-5/8" casing set at 2905 with 375 sacks 8% Gel and 100 sacks neat. Top of cement was indicated at 1750 by temperature survey. Casing was tested with 1000 psi before and after drilling plug with no drop in pressure. Test was therefore considered satisfactory. Drilling was resumed.

Witnessed by C. R. Nichols Stanolind Oil and Gas Company Production Foreman  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_  
day of \_\_\_\_\_ 19 \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

Name C. R. Nichols  
Position Production Foreman

Notary Public

Representing Stanolind Oil and Gas Company  
Company or Operator

My commission expires \_\_\_\_\_

Address Box 68 - Hobbs, New Mexico

Remarks:

Ray G. Galloway  
Oil & Gas Inspector  
Name  
Title

**APPROVED**  
OCT 26 1951

