

Form 9-331a
(March 1951)

TRIPPLICATE

(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office: Las Cruces
 Lease No: 051741 (b)
 Unit: U.S.G.
RECEIVED
MAR 30 1951
 OIL CONSERVATION COMMISSION
 HOBBS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico March 29, 1951
 W. C. Hawk B-10 No. 2-E
 Well No. 2-E is located 1920 ft. from [N] line and 660 ft. from [E] line of sec. 10
NE 1/4 Sec. 10 T18 R37E NEPTM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
North Brunson Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7950'. All casing points will be cemented in accordance with approved methods of the U. S. Geological Survey and any other requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated to surface. 7 5/8" casing to be set at approximately 3100' and cemented with approximately 1060 sacks or sufficient cement to protect the salt section. 5 1/2" to be set at total depth and cemented with approximately 660 sacks as determined by survey. 5 1/2" casing to be perforated opposite pay section.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title District Superintendent

100-100000
100-100000
100-100000

3

12	100-100000	100-100000	100-100000	100-100000	100-100000
100	100	100	100	100	100
100	100	100	100	100	100
100	100	100	100	100	100

of national goods will be about equal with the line a little of national goods at 2
as of business of the other goods in "100" and other goods will be counted in as
any other goods has given 100-100000 2 100-100000 2 100-100000 2 100-100000 2

to be placed in the following table: 100-100000 2 100-100000 2 100-100000 2
100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2
100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2
100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2

100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2

100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2

100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2

100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2

100-100000 2 100-100000 2 100-100000 2 100-100000 2 100-100000 2