

P. O. BOX 1920  
HOBBS, NEW MEXICO

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR  
CONOCO INC.

3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2130' F5L & 660' FEL  
AT TOP PROD. INTERVAL: ✓  
AT TOTAL DEPTH: ✓

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Information

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

NM 2512

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMF4

8. FARM OR LEASE NAME

Hawk B-3

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

McKee

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3 T-21S R-37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*In reference to the 9-7-82 Sundry Notice the producing formation of the subject well is the McKee and not the Blinbry/Drin Kard.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Butler TITLE Administrative Supervisor DATE 9-16-82

ACCEPTED FOR RECORD  
PETER W. CHESTER

APPROVED BY  
CONDITIONS OF APPROVAL IF ANY

SEP 22 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION  
P. O. BOX 1980  
HOBBS, NEW MEXICO 88240

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
*Cenoco*
3. ADDRESS OF OPERATOR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *2130' FSL & 660' FEL*  
AT TOP PROD. INTERVAL: ☒  
AT TOTAL DEPTH: ☒
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☒  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
*NM 2512*
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
*NMFU*
8. FARM OR LEASE NAME  
*Hawk B-3*
9. WELL NO.  
*4*
10. FIELD OR WILDCAT NAME  
*Blaineby / Drinkard*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
*Sec. 3, T-21S, R-37E*
12. COUNTY OR PARISH  
*Lea*
13. STATE  
*N.M.*
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.) 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*CO to 7830'. Set RBP @ 7825' and pkr. @ 7550'. Acidize 7612'-7820' w/ 20 bbls. 15% HCL-NE-FE in three stages. Divert w/ rock salt and benzoic acid. Flush w/ 50 bbls 2% KCL TFW. Swab. Release pkr, reset RBP @ 7595'. Spot 5' sand on top of RBP. Spot 3 bbls 15% HCL-NE-FE from 7582' - 7456'. Perf. w/ 15 SPF @ 7479', 86', 93', 98', 7507', 16', 32', 39', 46', 62', 68', 76', and 7582' (13 perfs). Set pkr. @ 7300'. Acidize 7479'-7582' w/ 26 bbls 15% HCL-NE-FE. Flush w/ 40 bbls 2% KCL TFW. Swab. Release pkr. & RBP. Install Production equipment. Test.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Wm. B. Butterfield* TITLE *Admin. Supervisor* DATE *9-7-82*

APPROVED BY *PETER V. CHENIER* (This space for Federal or State office use)  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_ DATE \_\_\_\_\_

SEP 10 1982

FOR  
JAMES A. GILHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

RECEIVED

SEP 13 1982

O.C.D.  
HOBBS OFFICE