



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Grid for well location with a circled '0' in the top right corner.

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES LOCATE WELL CORRECTLY

Coats & Jackson

(Ohio) J. W. Warlick

Well No. 1 in NE/4-NE/4 Sec. 19 T. 21S

R. 37E, N. M. P. M., Drinkard Field, Lea County.

Well is 990 feet south of the North line and 330 feet west of the East line of Sec. 19

If State land the oil and gas lease is No. No Assignment No.

If patented land the owner is J.W. Warlick, Address Hobbs, N.M.

If Government land the permittee is No, Address

The Lessee is (Ohio) J.W. Warlick, Address Hobbs, N.M.

Drilling commenced Aug 8, 1950 Drilling was completed Sept 17, 1950

Name of drilling contractor Coats & Jackson, Address Lubbock, Texas.

Elevation above sea level at top of casing 3525 feet.

The information given is to be kept confidential until nil 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to No. 2, from to No. 5, from to No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 6684 to 6691 feet. No. 2, from to feet. No. 3, from to feet. No. 4, from to feet.

CASING RECORD

Table with columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF SHOE, CUT & FILLED FROM, PERFORATED FROM TO, PURPOSE. Includes entries for 13-3/8 50# 8-Rd Natl 315 TexPt and 8-5/8 36# 8-Rd 2821 FB&C.

MUDDING AND CEMENTING RECORD

Table with columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

Table with columns: EXPLOSIVE OR CHEMICAL, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	190	190	Rock and Sand
190	315	125	Red Bed- Cemented Surface Pipe.
315	1200	885	Red Bed
1200	1270	70	Anhydrite
1270	1512	242	Anhydrite & Salt
1512	2475	963	Salt
2475	2740	265	Anhydrite
2740	2763	23	Lime
2763	2807	44	Anhydrite
2807	2821	14	Brown Lime - Run 8-5/8" Casing.
2821	2851	30	Lime
2851	3162	311	Sand & Lime
3162	3460	298	Anhydrite & Lime
3460	4445	985	Lime
4445	4508	63	Lime & Chert
4508	6691	2183	Lime
		6691 - -	T.D.