

COUNTY LEA FIELD Drinkard, Blinebry/ STATE N.M.

OPR PENROSE PRODUCTION COMPANY / & Penrose-Skelly MAP

2 Warlick

Sec. 19, T-11-S, R-37-E CO-ORD

990' fr N Line & 2310' fr E Line of Sec.

Spud 2-24-64; Comp 5-21-64 (G); CLASS EL 35337

| 5-20-64 (Bl & Drkd) | | FORMATION | DATUM | FORMATION | DATUM |
|------------------------|------|-----------|-------|-----------|-------|
| CSG & SX - TUBING | LOG: | Yates | 2620 | | |
| 13 3/8" 292' 300 | | Queen | 3396 | | |
| 9 5/8" 2560' 950 | | Penr | 3504 | | |
| 7" 6722' 811 | | Grayb | 3670 | | |
| | | Glor | 5176 | | |
| | | Clrk | 5716 | | |
| LOGS EL GR RA IND HC A | | Tubb | 6246 | | |
| | | TD | 6722' | | |

IP Grayburg Perms 3729-3846' Swbd 50 BOPD + 30 BW. Pot. Based on 24 hr test.

IP Blinebry Perms 5684-5988' Swbd 80 BOPD + 80 BLW. Pot. Based on 24 hr test.

IP Drinkard Perms 6673 thru 6679' F 144 BOPD + 26 EW. Pot. Based on 20 hr test of 121.50 + 22 BW thru 16.64" chk., CP Pkr, TP 450#.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT Cactus Drlg. Co. PROP DEPTH 6700' TYPE

DATE

- P.R. 2-20-64
- PD 6700' - Drinkard
- Contr - Cactus Drlg. Co.
- 3-2-64 Drlg. 3558'
- 3-8-64 TD 459', lost circ.
- 3-16-64 Drlg. 3872'
- Cored 3197-5238', rec 39' dolo., w/show oil throughout.
- 3-24-64 TD 6722', MORI.
- 3-30-64 TD 6722', prep to perf Blinebry
- Perf (Drinkard) @ 6678', 6678½', 6679' W/1 SPI
- Ac. 2000 gals.
- Swbd & Flwd 87 B NO
- Frac 8000 gals oil + 8000# sd. 6678-6679'
- Rec load + 270 BNO
- 4-6-64 TD 6722', flwg load from Blinebry
- Perf (Blinebry) @ 5684', 5685', 5723', 5724',
- 5742', 5743', 5745', 5762', 5763', 5772', 5773',
- 5777', 5778', 5789', 5858', 5859', 5877', 5878',
- 5890', 5891', 5910', 5911', 5916', 5917', 5930',

4-6-64 5931', 5967', 5968', 5973', 5974', 5987',
5988' W/1 SPI
Ac. 5000 gals.
Frac 73,000 gals wtr + 73,000# sd. (-1800 BLW)
4-12-64 TD 6722', flag load from Blinebry (-1200 BLW)
4-20-64 TD 6722', prep to Ac. Grayburg
Blinebry (-1100 BLW)
Perf (Grayburg) @ 3803½', 3805', 3806½', 3840'
3841' & 3846' W/1 SPI
4-28-64 TD 6722', swbg.
Ac. 1250 gals.
Frac 15,000 gals oil + 15,000# sd. 3803½-3846'.
Rec load.
Perf (Grayburg) @ 3729', 3731', 3732½', 3740'
3741', 3749' & 3750' W/1 SPI
Ac. 500 gals. (3729-50')

5-4-64 TD 6722', flag load.
Frac 15,000 gals oil + 15,000# sd. 3729-50'.
5-11-64 TD 6722', SI.
Load rec from perfs 3729-50'.
5-13-64 TD 6722', prep to triple complete.
5-15-64 TD 6722', W/1 Triple Completion.
5-1-64 TD 6722', COMPLETED.