

LEA
GULF OIL CORP.

Drinkard
13 Leonard, Harry (NCT-C)
Sec 36, T21S, R36E

NM
Page #2

3-15-76 TD 6806'; PBD 6764'; SI
Frac (6517-6703') 25,000 gals + 37,500# sd
3-22-76 TD 6806'; PBD 6764'; SI
Swbd down w/sli show gas (6517-6703')
Acid (6517-6703') 1000 gals
Frac (6517-6703') 30,000 gals wtr + 30,000# sd
3-29-76 TD 6806'; PBD 6764'; Tstg
Flwd 216 BO + 297 BW + 15 BFW in 72 hrs thru
32/64" chk, TP 50# (6517-6703')
4-5-76 TD 6806'; PBD 6764'; WO OCC Pot
Flwd 78 BO + 79 BW in 24 hrs thru 32/64" chk, TP
140# (6517-6703')
4-19-76 TD 6806'; PBD 6764'; Complete

4-4-14 NM

4-24-76

COMPLETION ISSUED

4-4-14 NM

IC 30-025-70010-76

COUNTY LEA FIELD Blinebry STATE NM 30-025-24023

OPR GULF OIL CORP.

MAP

13 Leonard, Harry (NCT-C)

Sec 36, T-21-S, R-36-E

CO-ORD

510' FNL, 1780' FEL of Sec

Spd 3-12-72

CLASS

EL 35132

Cmp 4-1-72

CSG & SX - TUBING

8 5/8" at 1243' w/400 sx

5 1/2" at 5885' w/540 sx

LOGS EL GR RA IND HC A

FORMATION

DATUM

FORMATION

DATUM

TD 5885'; PBD 5853'

IP (Blinebry) Perfs 5512-5827' F 166 BOPD. Pot based on 19 hr test thru 40/64" chk. GOR NR; Grav NR; CP 1250#; TP 50#

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran

PROP DEPTH 6000'

TYPE RT

DATE

F.R. 1-25-72; Opr's Elev 3505' GL

PD 6000' RT (Blinebry)

Contractor - Moran

3-13-72

TD 1243'; WOC

3-20-72

Drlg. 4898' lm

3-27-72

TD 5885'; PBD 5853'; Prep Perf

4-3-72

TD 5885'; PBD 5853'; Tstg

Perf @ 5518', 5540', 5571', 5630', 5655',
5692', 5827' w/4 SPI

Acid (5512-5827') 1750 gals

Frac (5512-5827') 50,000 gals wtr + 70,000# sd

Flwd 132 BO + 548 BLW in 18 hrs thru 40/64" chk,

CP 1250#; TP 50#

4-10-72

TD 5855'; PBD 5853'; COMPLETE

LOG TOPS: Anhydrite 1177', Yates 2632', Queen

3365', San Andres 3970', Blinebry 5510'

4-15-72

COMPLETION REPORTED