

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.	30-025-33547
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	MS 0004
7. Lease Name or Unit Agreement Name	
State	
8. Well No.	1
9. Pool name or Wildcat	BSW-Salado
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
DF 3469	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Brine
2. Name of Operator	Gold Star SWD Ltd Company
3. Address of Operator	Box 1480 Eunice, N.M. 88231
4. Well Location	Unit Letter <u>E</u> : <u>1340</u> Feet From The <u>N</u> Line and <u>330</u> Feet From The <u>W</u> Line
Section <u>15</u>	Township <u>21S</u> Range <u>37E</u> NMPM <u>Lea</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
DF 3469	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-28-96 Spudded 4 Pm. Derrick Floor 11'. Drilled 12 1/4" hole.

9-29-96 TD 1360' at 4:30 Pm. Ran 1344' 8 5/8" new 32# J55 casing, Float collar and Float Shoe, 5 Centralizers. Cement with 500 sx class C Premium W/ 4% Gel Mix and 300 sx class C Premium W/2% Calcium Chloride.

9-29-96 Circulated 236 sx cement to pit.

9-30-96 Pump cement plug down 12:30 AM.

10-1-96 WOC 18 Hr. 7:30 PM. Start drilling 7 7/8" hole.

10-2-96 TD 2200' at 6:00 AM.

10-3-96 Move rig. Run 2074' 2 7/8" Fiberglass tubing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Royce Crowell TITLE Mgr - Member DATE 10-4-96

TYPE OR PRINT NAME Royce Crowell TELEPHONE NO. 3942504

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE OCT 11 1996

CONDITIONS OF APPROVAL, IF ANY: