

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources

FORM C-103 Revised March 25, 1999

OIL CONSERVATION DIVISION 2040 South Pacheco Santa Fe, NM 87505

DISTRICT I 1625 N. French Dr., Hobbs, NM 88240
DISTRICT II 811 South First, Artesia, NM 88210
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410
DISTRICT IV 2040 South Pacheco, Santa Fe, NM 87505

WELL API NO. 30-025-34883
5. Indicate Type of Lease STATE FEE
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Northeast Drinkard Unit
8. Well No. 235
9. Pool name or Wildcat Eunice N., Blinebry-Tubb-Drinkard
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3499' GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: OIL WELL GAS WELL OTHER
2. Name of Operator Apache Corporation
3. Address of Operator 2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400
4. Well Location Unit Letter Lot 10 : 2800 Feet From The North Line and 1700 Feet From The East Line
Section 2 Township 21S Range 37E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:
Perform Remedial Work Plug and Abandon Remedial Work Altering Casing
Temporarily Abandon Change Plans Commence Drilling Operations Plug and Abandonment
Pull or Alter Casing Casing Test and Cement Job
Other Surface & Production Casing

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
7/15/00 MIRU UTI Rig # 302. Spud well @ 6:30 pm.
7/16/00 Drilled 12-1/4" hole to 1347'. Ran 33 jts 8-5/8" 24# J-55 ST&C casing. Cemented w/ 460 sx Class "C". Circulated 91 sx to pit.
7/27/00 Drilled 7-7/8" hole to 6370'. Ran 155 jts 5-1/2" 17# J-55 LT&C casing. Cemented w/ 725 sx 35/65 POZ "C" & 325 sx 50/50 POZ "H". Circulated 148 sx to pit. Top of float collar @ 6293'. Top of float shoe @ 6368'. Rig released @ 5:00 am.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Debra J. Anderson TITLE Sr. Engineering Technician DATE 7/28/00
TYPE OR PRINT NAME Debra J. Anderson TELEPHONE NO. 713-296-6338
APPROVED BY DATE 1 Aug 00
CONDITIONS OF APPROVAL, IF ANY: FIELD REP. II

CS

At

