

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

RECEIVED FEB 9 1948 HUBBS OFFICE

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

February 5, 1948

Place

Date

OIL CONSERVATION COMMISSION, Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company Baker \*B\* Well No. 10 in NW/4 SE/4

Company or Operator

Lease

of Sec. 10, T. 22S, R. 37E, N. M., P. M., Drinkard Field, Lea County.

The well is 2310 feet (N.) (E.) of the South line and 1650 feet (E.) (W.) of the East line of Section 10

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is A. B. Baker


Address Eunice, New Mexico

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary Tools.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing OD	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
15 1/2"	13-3/8"	40.5#	New	150'	Cemented	150
11 1/2"	9-5/8"	36#	"	2900'	"	1000
8 1/2"	7"	20#	"	5250'	"	400

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 5100 feet.

Additional information:

Halliburton process shall be used in cementing all casing.

Approved FEB 9 1948, 19 except as follows:

Sincerely yours,

Skelly Oil Company Company (or Operator)

By [Signature]

Position Dist. Supt.

Send communications regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By [Signature]

Title OIL & GAS INSPECTOR

ELF ELF