


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

W. H. Street Box 526, Midland, Texas
Company or Operator Address
Eugene Wood Well No. 4 NE 1/4 Sec. 22, T. 22S
Lease
R. 37E, N. M. P. M., Penrose Field, Lea County.
Well is 600 feet south of the North line and 660 feet west of the East line of Section 22
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Eugene Wood Address Abilene, Texas
If Government land the permittee is Address
The Lessee is W. H. Street Address Midland, Texas
Drilling commenced March 22, 1938 Drilling was completed May 26, 1938
Name of drilling contractor E. A. Duffy Address Abilene, Texas
Elevation above sea level at top of casing 3552 feet.
The information given is to be kept confidential until June 1, 1940

OIL SANDS OR ZONES

No. 1, from 3542 to 3550 No. 4, from 3550 to 3605
No. 2, from 3606 to 3609 No. 5, from to
No. 3, from 3625 to 3634 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 112 to 150 feet. 3 GPM
No. 2, from 607 to 730 feet.
No. 3, from 332 to 943 feet. 500' Water in Hole
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
12 1/2"	50	API Std	Repub	150'	Tex	Cemented			
8"	32	" "	Steel	1125'	Std	Cemented			
7" OD	24	" "	"	3553	"	Cemented			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	12 1/2"	150'	100	Halliburton		
8-7/8"	8"	1125'	150	"		
8-7/8" 67" OD	67" OD	3553	250	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	2000 gal	5/26/53		

Results of shooting or chemical treatment Acidized 2000 gallons, well showed 100 barrels through 2" upset tubing on 2 1/2" choke

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from Top feet to Bottom feet, and from feet to feet

PRODUCTION

Put to producing May 26, 1938
The production of the first 24 hours was 126 barrels of fluid of which 100% was oil; % emulsion; % water; and % sediment. Gravity, Be 55.5
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Chas. Clinton - Head Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 26th day of May, 1938, at Midland, Texas, Day 26, 1938
Name (S) W. H. Street
Position Owner & Operator
Representing Self Company or Operator
Address Box 526, Midland, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
2645	2665	20	anhy, red bed
2665	2695	30	anhy, lime
2695	2715	20	lime
2715	2735	20	lime, anhy
2735	2765	30	lime, anhy, broken
2765	2785	20	lime, gyp
2785	2805	20	lime, anhy
2805	2830	25	lime, anhy
2830	2840	10	lime, anhy
2840	2850	10	lime Bl. Inc. Gas
2850	2855	5	lime
2855	2880	25	lime, anhy, some blue shale
2880	2895	15	lime, little green shale
2895	2915	20	lime, anhy
2915	2930	15	lime, anhy
2930	2945	15	lime, anhy
2945	2964	19	lime, anhy
2964	2983	19	lime, anhy
2983	3000	17	lime, anhy
3000	3010	10	lime, anhy
3010	3030	20	lime, anhy
3030	3075	45	lime, anhy
3075	3088	13	gray lime
3088	3094	6	gray lime
3094	3108	14	gray lime
3108	3120	12	gray lime
3120	3129	9	gray & brown lime
3129	3109	80	gray lime
3109	3120	11	sandy lime
3120	3150	30	gray lime
3150	3180	30	gray lime
3180	3188	8	gray & brown lime
3188	3100	12	gray lime
3100	3109	9	gray lime
3109	3134	25	gray lime
3134	3150	16	gray lime
3150	3175	25	brown lime
3175	3180	5	gray lime
3180	3186	6	gray lime

sl. sh. gas @ 3125

sh. gas @ 3105

rainbow of oil

some oil & gas 3142-3150

Inc. gas 3107-3109

Gas, Inc. in oil 3125-3134

400 ft. in hole (oil)