

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Hondo Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
310 Old Santa Fe Trail, Room 206  
Santa Fe, New Mexico 87503

WELL API NO.

30-025-10460

5. Indicate Type of Lease

STATE

FEE ☒   
 ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil ☒

Gas ☐

Other ☐

2. Name of Operator

ANADARKO PETROLEUM CORPORATION

3. Address of Operator

PO BOX 2497, MIDLAND TX 79702-2497

4. Well Location

Unit Letter M 890 Feet From The SOUTH Line and 330 Feet From The EAST Line

Section 26

Township 22S

Range 37E

NMPN LEA

County

10. Elevation (Show whether DF, RKS, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

04-08-02 MOVED IN; RIGGED UP P & A EQUIP; NU BOP; RAN WITH TUBING; TAGGED UP @ 3,287'; PUMPED 75 SX CEMENT; DISPLACED TO 2,808'

04-09-02 TAGGED CEMENT @ 2,949'; CIRCULATED HOLE WITH 120 bbls OF MUD; PULLED UP TO 2,470'; PUMPED 25 SX CEMENT; DISPLACED TO 2,311'; PULLED OUT WITH TUBING; PERFORATED @ 1,300'; SET PACKER @ 1,164'; SQUEEZED 25 SX OF CEMENT; DISPLACED TO 1,200'

04-10-02 TAGGED CEMENT @ 1,186'; LAID TOWN TUBING AND PACKER; PERFORATED @ 260'; PUMPED 85 SX CEMENT WITH 2% CaCl; WOC 3 HRS; TESTED TO 500#; GOOD; PUMPED 10 SACKS 60' TO SURFACE; RIGGED DOWN; CUT OFF WELLHEAD; INSTALLED DRY HOLE MARKER.

I hereby certify that the information above is true and correct to the best of my knowledge and belief.

SIGNATURE R. N. Mueller TITLE Sr Staff Production Engineer DATE 04/17/02

TYPE OR PRINT NAME R. N. Mueller

TELEPHONE NO. 915/683-0555

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

COMPLIANCE OFFICER

JUN 10 5 2002