

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

P.O. Box 1980

Albuquerque, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen SEP entry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE
BUREAU OF LAND MGMT.
ALBUQUERQUE, NEW MEXICO

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco E & P

3. Address and Telephone No.

P.O.Box 3109 Midland, Texas 79702 (915) 688-4492

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660 FSL, 1980 FEL, Sec. 20 T22S R38E Unit Letter O

5. Lease Designation and Serial No.
LC 032104

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

A.H. Blinbry Fed NCT-1 #4

9. API Well No.

30-025-12141

10. Field and Pool, or Exploratory Area

Bunson Drinkard

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☒ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8-14-98 Notify BLM of intent to plug, MIRU, RIH w/2 7/8 CIBP in E string to 5750', set CIBP--Set down in W string @ 2315', Set down in N string @ 1365'

8-17-98 RIH w/bit & scraper in N string to 6000', POOH, well started to flow, SION

8-18-98 Kill N string, POOH w/tbg, RIH w/2 7/8 CIBP, set @ 5630' in N string, RIH w/bit & scraper in W string, set down @ 2315', work tbg, solid, POOH w/tbg

8-19-98 Rig up reverse unit, RIH w/bit & scraper, C/O W string to 2452' getting metal returns.

8-20-98 BLM okayed 10 sx cement @ 2452' in W string, RIH N string, mix salt gel fm 5630', spot 10 sx cement on CIBP @ 5630, PUH to 5200' spot 10 sx cement, PUH to 2600' spot 10 sx cement, POOH, RIH E string tag CIBP @ 5750' SION

8-21-98 Mix and pump salt gel in E string, spot 20 sx cement @ 5750', PUH to 5200' spot 10 sx cement, PUH to 2600' spot 10 sx cement, POOH, RIH w/cutter in W string, tag cement @ 1832', cut 2 7/8 @ 1831', RIH w/cutter in N string, tag cement @ 2211', cut 2 7/8 @ 1831', RIH w/cutter, tag cement @ 2250', cut 2 7/8 @ 1831', SION

8-24-98 Lay down N string, Lay down E string, Lay down W string, RIH w/work string to 1831', SION

8-25-98 Mix and spot 100 sx cement, displace to 1500' WOC 4 hrs, RIH to 1886', no cement, POOH

8-26-98 RIH w/tbg, tag top of 2 7/8 @ 1831', pick up tbg RIH beside csg to 2524', circulate w/170 bbls 9.8#mud

8-31-98 Mix and pump 200 sx cement @ 2520, POOH w/tbg WOC 4 1/2 hrs, RIH w/tbg, tag cement @ 1548', PUH to 1408'

9-01-98 Mix and spot 50 sx cement @ 1408' POOH w/tbg, Mix and spot 20 sx cement 60' to surface in 9 5/8 casing, RDMO

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title Manager, Dawson Petroleum Services, P&A Div.

Date 09/08/98

(This space for Federal or State Office use)

(ORIG. SGD.) ALEXIS C. SWOBODA

Title PETROLEUM ENGINEER

Date

Approved by
Conditions of approval, if any:

OCT 08 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side