

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.W. Oil Cons.
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco E&P Inc.

3. Address and Telephone No.

P.O. Box 3109 Midland, Texas 79702 (915) 688-4492

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990 FNL 330 FEL Sec 29 T22S R38E Unit Letter A

5. Lease Designation and Serial No.

41655

6. If Indian, Allotment or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. #28
A.H. Blinbry Fed NCT-1#2

9. API Well No.

30-025-21406

10. Field and Pool, or Exploratory Area

Brunson Drinkard Abo

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Notify BLM of intent to plug

2. MIRU on Z string NU BOP

3. Set 2 7/8" CIBP @ 6950' w/20' cement

4. RIH circulate hole w/9.8# mud

5. 10 sx cement 6100-6000

6. 10 sx cement 5600-5500

7. 10 sx cement 5200-5100

8. 10 sx cement 2600-2500

9. POH RU on Y string

10. Set CIBP @ 5630' w/20' cement

11. RIH circulate hole w/9.8# mud

12. 10 sx cement 5200-5100

13. 10 sx cement 2600-2500

14. Cut and pull 2 7/8" casing @ 1700'± (Z&Y)

15. 50 sx cement 1380-1180 WOC/tag (salt/shoe)

16. 10 sx cement 30' to surface

17. RDMO, cut off well head, install dry hole marker, clean location.

14. I hereby certify that the foregoing is true and correct

Signed

Title Reservoir Engineer

Date 4/28/98

(This space for Federal or State office use)

Approved by CRIG SGD GARY GOURLEY

Title PETROLEUM ENGINEER

Date 4/28/98

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

RECEIVED
1998 MAY -4 P 2:47
BUREAU OF LAND MGMT.
HOBBS, NEW MEXICO
Y-Blinbry/tub
Z-Drinkard/Abo