

COPIES RECEIVED		
CONTRIBUTION		
STATE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator John H. Hendrix	8. Farm or Lease Name Cossatot K
3. Address of Operator 403 Wall Towers West, Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER F, 2310 FEET FROM THE north LINE AND 1650 FEET FROM THE west LINE, SECTION 7 TOWNSHIP 22-S RANGE 38-E NMPM.	10. Field and Pool, or Wildcat Wantz Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3344.8' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. TD @ 7650'.
2. Ran 274 jts. (7660.45') 5-1/2" csg., 15.5, 17#, 20# csg., set @ 7650'.
3. Cemented w/500 sxs. Class C 50-50 Pozmix 2% gel, 8# salt/sx., 220 sxs. Halliburton "Lite" and 100 sxs. Halliburton "Lite" w/1/4# flo sal, 15# salt/sx. Plug down @ 7:45 p.m. MDT 3-25-74.
4. Top of cement @ 2890'.
5. Tested well to 800# - ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Marlene L. Jones TITLE Production Clerk DATE 3-27-74

APPROVED BY Joe D. [Signature] TITLE Dist. 1, Supv. DATE           

CONDITIONS OF APPROVAL, IF ANY: