

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
P. O. BOX 1930  
HOBBS, NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other2. NAME OF OPERATOR  
ESTORIL PRODUCING CORPORATION3. ADDRESS OF OPERATOR  
11th Floor, Vaughn Bldg., Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Sec. 10, 660' FSL &amp; 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) PROGRESS REPORT

5. LEASE

88240  
13838

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ALTA FEDERAL

9. WELL NO.

ONE

10. FIELD OR WILDCAT NAME

UNDESIGNATED BONES SPRINGS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T20S, R34E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3389.9' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 8-3-82 RU WL unit. Ran Radio active tracer svy. & temp. svy. Survey indicated major channeling up hole to 7010'. Slight channeling up to 6998'. Major channeling dn hole at 7040' & slight channeling dn to 7050'. Used 90 BW to run tracer svy.
- 8-5-82 RU Haliburton frac equip. Fraced perf. fr. 7017-29 w/15,000 g. of gelled wtr. & 2500# of 20/40 Sd & 14,000# of 12/20 Sd. Max. trtg. press. 4250#, min. 3700#, avg. rate 2.6 BPM. ISDP 1060# 15" 940#.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*David R. Glass*

TITLE CLERK

DATE 8-10-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

OCT 17 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

SERVICE  
MEXICO

RECEIVED

OCT 15 1982

O.C.D.  
HOBBS OFFICE