WELL DATA SHEET

| SECTION COUNTY STATE COUNTY STATE Date Completed SET 100 Set 1 Section Sect | LEASE & WELL NO | DRINKARD (NCT-B) #7 | FIELD/POOL BLINE | BRY / TUBB | DATE |
|--|-----------------|---|---------------------|----------------|-----------------|
| Date Completed Initial Formation From: to GOR OR to GE OR to GR Or to Gertinal bod or Completion Data: IO34 | LOCATION | FEET FROM | LINE AND | FEET FROM | LINE |
| Subsequent Workover or Reconditioning: Subsequent Workover or Reconditioning: | SECTION | | | | |
| Subsequent Workover or Reconditioning: Subsequent Workover or Reconditioning: | | GE' KDB to GE' DF to GE' | | | GORbwpd_dd_@psi |
| 5800' TUBING AS BELOW 5900' 24%' 4.70# J-55 ELE BRD w/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINERY (Approximate Depths) Fresent Inj. bwpd @ psi Date bopd bwpd Date GAS MCFPD 7" BAKEE LOKSET PACKER w/ ON-OPF TOOL @ ± 5900' TUBB (Approximate Depths) 5950' to 6270' 7 " OD # Thd Cr. " OD # Thd Csg. | | 103/4 " OD Surface Pipe set @ 'w/ sx Cmt. Circulated? | | | |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) | | | Subsequent Workover | or Recondition | ning: |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) Fresent Inj | | | | | |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) | | | | | |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) | | | | | |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) | | | | | |
| S900' 23/8" 4.70 # J-55 EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY (APPROXIMATE DEPTHS) Fresent Inj | | | | | |
| EUE 8RD W/ BEVELED COUPLINGS TUBING DUAL TUBING ANCHOR @ ± 5550' BLINEBRY Present Inj. bwpd @ psi Date bopd bwpd Date S600' to 5800' TUBB Lokset Packer W/ On-off Tool @ ± 5900' TUBB (Approximate Depths) 5950' to 6270' Thd Gr | | 5800' TUBING AS BELOW | | | |
| BLINEBRY (APPROXIMATE DEPTHS) S600' to 5800' BLINEBRY Present Inj | | EUE BRD W/ BEVELED | | | |
| APPROXIMATE DEPTHS) SGOO' to 5800' TUBB (Approximate Depths) 5950' to 6270' Thd Gr | × × | DUAL TUBING ANCHOR @ = 5550' | | | |
| TUBB (Approximate Depths) 5950' to 6270' Thd Gr Csg. | | # (APPROXIMATE DEPTHS) | | bopd | bwpd Date |
| 7 " OD # Thd Gr,Csg. | | W/ON-OFF TOOL @ \$ 5900' | | | |
| Gr,Csg | | |) | | |
| PBD set @ 'w/ sx TD Cmt Circulated? TOC @ by TS | | Gr. , Csg ' set @ 'w/ sx Cmt Circulated? | | | |