## MEXICO OIL CONSERVATION C $N_{\lambda}$

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON REPAIRING WELL

REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON PULLING OR OTHERWISE ALTERING CASING REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL REPORT ON RESULT OF TEST OF CASING SHUT-OFF REPORT ON DEEPENING WELL X REPORT ON RESULT OF PLUGGING OF WELL May 29, New Mexico 1937 Hobbs. OIL CONSERVATION COMMISSION. Santa Fe, New Mexico. Gentlemen: Following is a report on the work done and the results obtained under the heading noted above at the. Sims "C" Skelly Oil Company in the Company or Operator CSE/4, SW/4 Lea Skelly Area May 23, 24, 25, 1937 The dates of this work were as follows: .19.37 Notice of intention to do the work was they not submitted on Form C-102 on\_ and approval of the proposed plan was was believed. (Cross out incorrect words.) DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED After losing bit in hole and being unable to drill by, hole was plugged back from 3387' to 1805' w/ 200 sx cement by Halliburton Process & 1795' of 7"OD csg. was pulled. Whipstock set at 1796' & while drlg. to 1850' went back into old hole.aDecided to plug and abandon. Pulled 857 of 8-5/8" csg. & 44' of 16" csg. Hole was cemented & mudded w/ 100 sx of cement from 1850 to surface to shut off water sands & to protect top of salt. Cellar was cemented and a joint of 4" pipe was cemented into the cellar and left standing 4' above the surface of the ground to serve as a marker for the junked and abandoned well. Machine was then moved 80' North and 20' East of plugged hole to start drilling new well. Clower Drilling Co. J.C.Clower Witnessed by-Company Title I hereby swear or affirm that the information given aboveis true and correct. Subscribed and sworn to before me this. May Name Position Notary Public Skelly Oil Company Representing. Company or Operator Dec. 10, 1940 Hobbs. New Mexico My Commission expires. Address Remarks:

## PARET DO TODONO CHEROLES

the state of the state of the state of the second state of

 $\frac{1}{2} \frac{1}{2} \frac{1$ 

(1) 等性,更多的,因为,因为,是是**是我**的一种,不是是

edicinate di series de la companya d

Bearing to the

to the second of the second of

1. 新日本 1. 2000 年 1900年 1910年 1910年

in the confidence of the control of

Land Control of the C Same Same 7.5

• The second second

and the entrem The state of the second in the second of the second of

+ t