

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Jalmat Formation Yates - Seven Rivers County Lea
 Initial _____ Annual _____ Special X Date of Test May 9, 1958
 Company Amerada Petroleum Corporation Lease Cagle "C" Well No. 1
 Unit D Sec. 3 Twp. 26 Rge. 37 Purchaser Kl. Paso Natural Gas Company
 Casing 5-1/2 Wt. 15.5 I.D. _____ Set at 3314 Perf. 2600 To 3195
 Tubing 2-3/8 Wt. 4.7 I.D. _____ Set at 2604 Perf. _____ To _____
 Gas Pay: From 2600 To 3195 L 2604 xG 0.655 -GL 1706 Bar.Press. _____
 Producing Thru: Casing _____ Tubing X Type Well Single
Re- Single-Bradenhead-G. G. or G.O. Dual
 Date of Completion: 5-20-56 Packer 2592 Reservoir Temp. _____

OBSERVED DATA

Tested Through (~~Proven~~) (~~Choice~~) (Meter) Type Taps _____

| No. | Flow Data | | | Tubing Data | | Casing Data | | Duration of Flow Hr. | |
|-----|---|--|----------------|-------------------------|--------------|----------------|--------------|----------------------|----------------|
| | (Proven) (Line) Size | (Standard) (Orifice) Size | Press. psig | Diff. h _w | Temp. °F. | Press. psig | Temp. °F. | | Press. psig |
| SI | | | | | | 612 | | | 72 |
| 1. | 4 | 1.000 | 569 | 2.56 | 83 | 602 | | | 24 |
| 2. | 4 | 1.000 | 567 | 13.69 | 80 | 587 | | | 24 |
| 3. | 4 | 1.000 | 564 | 17.64 | 83 | 583 | | | 24 |
| 4. | 4 | 1.000 | 563 | 27.56 | 82 | 566 | | | 24 |
| 5. | | | | | | | | | |

FLOW CALCULATIONS

| No. | Coefficient (Flg.) (24-Hour) | $\sqrt{h_w P_f}$ | Pressure psia | Flow Temp. Factor F _t | Gravity Factor F _g | Compress. Factor F _{pv} | Rate of Flow Q-MCFPD @ 15.025 psia |
|-----|------------------------------|------------------|---------------|----------------------------------|-------------------------------|----------------------------------|------------------------------------|
| 1. | 6.135 | 38.60 | | .9786 | .9571 | 1.053 | 234 |
| 2. | 6.135 | 89.11 | | .9813 | .9571 | 1.053 | 541 |
| 3. | 6.135 | 100.89 | | .9786 | .9571 | 1.053 | 611 |
| 4. | 6.135 | 126.00 | | .9741 | .9571 | 1.052 | 758 |
| 5. | | | | | | | |

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio Dry cf/bbl. Specific Gravity Separator Gas 0.655
 Gravity of Liquid Hydrocarbons _____ deg. Specific Gravity Flowing Fluid _____
 F_c 9.936 (1-e^{-s}) .111 P_c 625.2 P_c 390.9

| No. | P _w P _t (psia) | P _t ² | F _c Q | (F _c Q) ² | (F _c Q) ² (1-e ^{-s}) | P _w ² | P _c ² -P _w ² | Cal. P _w | P _w /P _c |
|-----|--------------------------------------|-----------------------------|------------------|---------------------------------|--|-----------------------------|--|---------------------|--------------------------------|
| 1. | 615.2 | 378.5 | 2.33 | 5.43 | 0.60 | 379.1 | 11.8 | 616 | .9853 |
| 2. | 608.2 | 370.2 | 5.38 | 28.94 | 3.21 | 363.4 | 27.5 | 603 | .9845 |
| 3. | 596.2 | 355.5 | 6.07 | 36.84 | 4.89 | 359.6 | 31.3 | 600 | .9837 |
| 4. | 579.2 | 335.5 | 7.53 | 56.70 | 6.29 | 341.8 | 49.1 | 585 | .9827 |
| 5. | | | | | | | | | |

Absolute Potential: 7600 MCFPD; n .9989819

COMPANY Amerada Petroleum Corporation
 ADDRESS Drawer D - Monument, New Mexico
 AGENT and TITLE H. G. Kidd District Engineer *H. C. Kidd*
 WITNESSED Earl G. Smith
 COMPANY Kl. Paso Natural Gas Company

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressibility factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .