

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction.
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Federal LC 030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. E. Lammyon

9. WELL NO.

30

10. FIELD AND POOL, OR WILDCAT

Tongue Blinberry

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T-23S, R-37E

12. COUNTY OR PARISH

Lee

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	14. PERMIT NO. Dated 2-27-68	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3303.5 KB
2. NAME OF OPERATOR Gulf Oil Corporation		
3. ADDRESS OF OPERATOR P. O. Box 980, Kermit, Texas 79745		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWL and 660' FWL		

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Displaced hole w/135 bbls mod brine and spotted 500 gals NE acid.
Perforated w/4 - 0.45" JEPF 5556-58', 5636-38' and 5728-30'. Pumped
3,000 gals 7-1/2% NE acid w/1 - 1" RCN ball sealer every 120 gals.
IR 4.5 BPM. Frac down 5-1/2" OD casing w/20,500 gals gelled brine,
30,750# 20-40 sand, 1,000 gals 15% NE acid and 24 - 1" RCN balls
flushed w/136 bbls brine. AIR 30.5 BPM @ 2350 psi. Ran 2-3/8" OD
tubing to 5748'. Swabbed well in. Flowed 278 BO, 16 BW, 498 MCF in
24 hours on 26/64" choke, 400 psi, FIP on test ending 4-1-68. GOR =
1791. Gravity 39.1°.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. E. Fidler

TITLE Area Engineer

DATE April 2, 1968

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

APR 4 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.