

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFG. NO.	NO. SUB.
a	double upset bolt s/sq, nut, round washer, and cotter key on short end, sq, nut and HF locknut on long end, 1 1/8" long (or length required.) wet process porcelain secondary spool insulator.	7828			
b	3" brown glass required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-18 Note: provide clamp and ground conduit parallel groove clamp, size req'd		J101	FUNBY SERVIC "UC"	
d	secondary insulator clevis for 4" insulator 3/8" thimbleye nut 5/8" x 12" (or length req'd) straight thimbleye bolt w/sq. nut	6510 5512			
e	transformer cluster mount bracket (small)			ALUMFORM 6M3-6	X
f	transformer cluster mount bracket (large)			ALUMFORM 15M3-6	X
g	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. Dwg No. ES-19				
h	16" cross plate anchor (or size req'd)	X-16			
i	8-way expanding anchor (size req'd)	88135			
j	4" brown glass wet process porcelain secondary spool insulator		J0101		
k	5/8" x 7" thimbleye anchor rod w/nut (use twineye if req'd - Chance No. 5347)	5317 (nut 5506P)			
l	3/8" high strength guy strand (10,800 lb.)				
m	performed guy grip for 3/8" guy strand	5010			
n	5/8" x 10" angle thimbleye bolt w/nut	6813 1/2			X
o	3"x3"x1/4"x11/16" hole curved washer				
p	6" - guy clamp w/3-1/2" bolts	6454			
q	medium size strain insulator	7887			X
r	serving sleeve for 3/8" guy strand				
s	3/16" x 2-1/2" x 7" lift plate				
t	pole bottom ground plate (may use butt-wrapp if desired)				
u	Ground Connection (See Dwg. ES-12)				
v	wet process porcelain secondary spool insulator, 3" - white glass				
w	wet process porcelain secondary spool insulator, 4" - white glass				

DATE: 12-27-71	TITLE: DESCRIPTION MATERIALS
DRAWN BY: E. WINTER	CONOCO HOBBS DIVISION
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	JOB: ELEC SPECS
	DRAWING NO: ES-1
	SHEET 3 OF 3

RECEIVED

JUN 14 1977

U.S. CONSERVATION COMM.
HOBBBS, H. M.