

N. M. OIL CONS. COMMISSION

P. O. BOX 1820

UNITED STATES HOBBS, NEW MEXICO 88240

Form Approved.  
Budget Bureau No. 42-R1424

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
CONOCO INC.
3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL 1980' FWL  
AT TOP PROD. INTERVAL:   
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) TD, ran production csg. ☒

SUBSEQUENT REPORT OF:



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
LC-068281(6)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Russell Federal 17 Federal
9. WELL NO.  
12
10. FIELD OR WILDCAT NAME  
East Mason Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17, T-26S, R-32E
12. COUNTY OR PARISH 13. STATE  
Lea NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Reached TD of 4502' on 3/4/82. Ran 5 1/2", 15.5 # and 17 #, D-55 csg set at 4494', DV 2458'. Cemented in 2 stages: 1st stage: 300sx Class C lite w/ 18% salt, tail w/ 200sx Class C w/ 2% CaCl<sub>2</sub>. 2nd stage: 700sx Class C lite w/ 18% salt, tail w/ 200sx Class C w/ 2% CaCl<sub>2</sub>. Circulated 225sx to surface.

ACCEPTED FOR RECORD

APR 27 1982

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Wm. A. Patterson

TITLE Administrative Supervisor

DATE March 10, 1982

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE