Form 9-330
(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

RECEIVED

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DRY [ ] Other

b. TYPE OF COMPLETION: NEW WELL [X] WORK OVER [ ] DEEP-EN [ ] PLUG BACK [ ] DIFF. RESVR. [ ] Other

2. NAME OF OPERATOR: Chevron U.S.A. Inc.

3. ADDRESS OF OPERATOR: P.O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface: Unit A, 1310' FNL and 210' FEL
At top prod. interval reported below
At total depth

5. LEASE DESIGNATION AND SERIAL NO.: LC030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: C. E. LaMunyon

9. WELL NO.: 50

10. FIELD AND POOL, OR WILDCAT: Teague/Blinebry

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec.28, T23S,R37E

12. COUNTY OR PARISH: Lea

13. STATE: NM

14. PERMIT NO.:

DATE ISSUED: 12-8-89

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
2/16/89	3/15/89	4-9-89	3288'	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
5960	5870		→	X	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
Teague/Blinebry 5314, 5661

25. WAS DIRECTIONAL SURVEY MADE: ---

26. TYPE ELECTRIC AND OTHER LOGS RUN: CBL/CET w/GR & CCL

27. WAS WELL CORED: yes

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	1080'	12 1/4"	675sx Cl C	
5 1/2"	15.5#	5960'	7 7/8"	1stg 100sx lead 690sx tail	
				2stg 870sx lead 175sx tail Class C	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	5624'	

31. PERFORATION RECORD (*Interval, size and number*)
5314, 5322, 5331, 5565 & 5661 @ 1JHPF
5 holes total. 5360,65,71,76,82,86,
5400,04,08,49,59,76,84,92,5546,5749,
1 JHPF, 0°, 17 holes.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5314-5661	2500 gal 15% NEFE
"	Frac w/22,000 gal 40# Xlink & 41,000# 20/40 sd, & 6,000# 20/40 RCS.
5314-5749	4000 gallons NEFE HCL.

33.*

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
4-9-89	Pumping-2 x 1 1/2 x 20 RHBC	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
7-6-89	24	2" WO	→	9	65	63	7222

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
40#	40#	→	9	65	63	37.2

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): Sold

TEST WITNESSED BY:

35. LIST OF ATTACHMENTS

SDS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED K. K. Elsner TITLE Technical Asst. DATE 4-10-89

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement"*: Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
BLINEBRY	5298	5930	ANHYDRITIC DOLOMITE; OIL + GAS SHOWS
CORE (BLBR)	5278	5398	" " " "
CORE (BLBR)	5455	5586	" " ; SCATTERED OIL + GAS SHOWS w/ LOCALIZED, SUBTLE FRACTURES.

38. GEOLOGIC MARKERS

NAME	TOP MEAS. DEPTH	TOP TRUE VERT. DEPTH
RUSTLER	1033	SAME
TANSALT	1147	↓
YATES	2568	
7 RIVERS	2755	
QUEEN	3261	
GRAYBURG	3531	
SAN ANDRES	3789	
GLORIETA	4940	
BLINEBRY	5298	
TUBB	5930	

RECEIVED
JUL 31 1989
OCD
HOBBS OFFICE

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-683636