

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

**OIL CONSERVATION DIVISION**  
310 Old Santa Fe Trail, Room 206  
Santa Fe, New Mexico 87503

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30 025 33717
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name  State 19
8. Well No. 1
9. Pool name or Wildcat Wildcat - Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3541' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

2. Name of Operator  
Cobra Oil & Gas Corporation

3. Address of Operator  
P.O. Box 8206 Wichita Falls, Texas 76307-8206

4. Well Location  
Unit Letter G : 1865 Feet From The North Line and 2165 Feet From The East Line  
Section 19 Township 24S Range 33E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK  PLUG AND ABANDON

TEMPORARILY ABANDON  CHANGE PLANS

PULL OR ALTER CASING

OTHER: \_\_\_\_\_

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK  ALTERING CASING

COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB

OTHER: \_\_\_\_\_

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 12 1/4" hole to 12,480', 3/19/97. Run hole logs, loggers total depth 12,480'. Run 9 5/8" 53.5 # P110 LT & C casing and set at 12,480'. Rig up Halliburton and cement with 1850 sacks class "H" cement w/3% Econolite, 1/2#/sack Flocele and 5% salt, tail in with 400 sacks of 50/50 Poz "A" w/2% gel, 3% KCL and .5% Halad-322. Plug down 1:45 AM 3/22/97. Test casing to 2600 psi for 45 minutes 3/25/97. Drill 8 1/2" hole out of 9 5/8" casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rory Edwards TITLE Production Supervisor DATE 3/26/97  
TYPE OR PRINT NAME Rory Edwards TELEPHONE NO. (817) 716-5100

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE ORIGINAL SIGNED BY GARY WINK FIELD REP. II DATE MAR 31 1997

CONDITIONS OF APPROVAL, IF ANY:

