

District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-101  
Revised October 18, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address GRUY PETROLEUM MANAGEMENT COMPANY P.O. BOX 140907 IRVING, TEXAS 75014-0907		OGRID Number 162683
Property Code 22874	Property Name RHODES STATE COM.	API Number 30-025-34417
		Well No. 5

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	Country
C	16	26S	37E		660'	North	1980'	West	LEA

Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	Country
Proposed Pool 1 RHODES YATES 7RIVERS-GAS (83810)					Proposed Pool 2				

Work Type Code N	Well Type Code G	Cable/Rotary R	Lease Type Code S	Ground Level Elevation 2978'
Multiple NO	Proposed Depth 4000'	Formation YATES-7RIVERS	Contractor UNKNOWN	Spud Date WHEN APPROVED

Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
25"	20"	NA	40'	Redi-mix	Surface
12 1/2"	8 5/8"	24	750'	400 Sx.	Surface
7 7/8"	5 1/2"	15.5	4000'	1000 Sx.	Surface

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
2. Drill 12 1/2" hole to 750'. Run and set 750' of 8 5/8" 24# J-55 ST&C casing. Cement with 400 Sx. of Class "C" Halco Light + additives, tail in with 200 Sx. of Class "C" + 1/2# flocele/Sx. + 2% CaCl, circulate cement to surface.
3. Drill 7 7/8" hole to 4000'. Run and set 4000' of 5 1/2" 15.5# J-55 ST&C casing. Cement in two stages: 1st stage cement with 400 Sx. of Class "C" + 3# salt/Sx., + 1/2# flocele/Sx. 2nd stage cement with 600 Sx. of Class "C" Halco Light + 9# salt Per Sx. + 1/2# flocele/Sx. , circulate cement to surface.

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Joe T. Janica*  
Printed name: Joe T. Janica  
Title: Agent

Date: 06/03/98 Phone:

OIL CONSERVATION DIVISION	
Approved by: CHRIS WILLIAMS	Supervisor
Approval Expires: 09 1998	Expiration Date: